



New Massey Ferguson® 1529 & 1532 Compacts

Now with Hydrostatic Transmission



The only way to go. And go. And go.

New for 2010 – Three-Range Hydrostatic Transmissions on the Massey Ferguson 1529 and 1532 compact tractors.



A Hydrostatic Transmission is the ideal choice for turf mowing or jobs requiring constant speed and directional changes within a small area.



Standard features on the 1529 and 1532 with Hydrostatic Transmission include, cruise control and a factory installed joystick.



Separate forward and reverse pedals on the uncluttered platform are easy to operate and offer infinite ground speeds. Increasing engine speed is as simple as pushing the pedal. We also moved the brake pedals to the left side of the platform for ease in using the steering brakes.



MASSEY FERGUSON

masseyferguson.com



MASSEY FERGUSON is a worldwide brand of AGCO.

MF10P008 (01) 5 MT

TRACTOR MODEL	1529 4WD PLATFORM	1532 4WD PLATFORM
Engine		
Gross engine HP	28	32.5
PTO HP	21.7	24.5
Rated engine speed	2,500	2,600
Type	3-cylinder diesel	3-cylinder diesel
Displacement: in. ³ (cc)	91.4 (1,498)	91.4 (1,498)
Cooling system	Liquid cooled	Liquid cooled
Fuel tank capacity: gal (L)	9.2 (35)	9.2 (35)
Transmission options		
Hydrostatic w/Cruise	3 range	3 range
Rear brakes	Wet disc	Wet disc
PTO		
Rear PTO type	Ind. 540 RPM	Ind. 540 RPM
Control	Electro-hydraulic	Electro-hydraulic
Mid PTO type	2,000 RPM (opt.)	2,000 RPM (opt.)
Hydraulics		
Type of system	Open center	Open center
Flow at remotes: gpm (lpm)	8.1 (30.7)	8.5 (32.2)
Pwr steering flow: gpm (lpm)	3.4 (12.9)	3.6 (13.6)
Total flow: gpm (lpm)	11.5 (43.6)	12.1 (45.8)
Factory-installed joystick	Standard	Standard
Rear auxiliary remotes	1 or 2 spool (opt.)	1 or 2 spool (opt.)
3-point hitch		
ASAE hitch	Cat. I	Cat. I
Controls	Position	Position
Rate of drop control	Standard	Standard
Lift capacity @ hitch point: lbs. (kg)	2,425 (1,100)	2,425 (1,100)
Type of stabilizers	Turnbuckle	Turnbuckle
Type of link ends: 2wd/4wd	Fixed	Fixed
Operator area		
Platform type	Semi-flat isolated	Semi-flat isolated
ROPS	Folding	Folding
Seat type	Suspended	Suspended
Seat belt type	Retractable	Retractable
Hood type	Flip up	Flip up
Dimensions with ag tires		
Overall length: in. (mm)	120.7 (3,055)	120.3 (3,055)
Minimum overall width: in. (mm)	58.1 (1,475)	58.1 (1,475)
Maximum height over ROPS: in. (mm)	97 (2,465)	97 (2,465)
Ground clearance: in. (mm)	10.4 (265)	10.4 (265)
Wheelbase: in. (mm)	66.7 (1,695)	66.7 (1,695)
Shipping weight: lbs. (kg)	2,657 (1,205)	2,657 (1,205)

See our 1500 Series brochure for full Series specifications.