

# LS Tractor

## MT125 COMPARISON



MAKE MODEL	<b>LSTRACTOR</b> MT125 (2017-Present)	<b>JOHN DEERE</b> 1023E (2011-Present)	<b>KIOTI</b> CS2210 (2016-Present)	<b>KUBOTA</b> BX2380 (2017-Present)	<b>MASSEY FERGUSON</b> GC1723E (2019-Present)
<b>ENGINE PERFORMANCE</b>					
Advertised Engine Power, Rated, hp (kW)	24.7 (18.4)	22.4 (16.5)	21.1 (15.7)	23 (17.1)	22.5 (16.8)
Fuel Tank capacity, gal (L)	6.6 (25)	5.6 (21.2)	6.7 (25.5)	6.6 (25)	6.6 (25)
<b>PTO PERFORMANCE</b>					
PTO Horsepower, Basic / Optional Transmission, hp (kW)	17.2 (13)	15.3 (11.4)	18.7 (13.9)	17.7 (13.2)	18.3 (13.6)
PTO Speeds, rpm	540	540 Rear; 2100 Mid	540	540	540
<b>BASIC ENGINE</b>					
Engine Make	Yanmar	Yanmar	IHI Shibaura	Kubota	Iseki
Displacement, cu in (L)	77.3 (1.267)	60.6 (0.993)	69 (1.131)	54.8 (0.898)	68.5 (1.123)
<b>BASIC TRANSMISSION CONFIGURATION</b>					
Transmission Type	Hydrostatic, dual pedal	Hydrostatic	Hydrostatic		2-range w/ cruise control
Number of Forward / Reverse Speeds	Infinite, 2 ranges	Infinite, 2 ranges	Infinite, 2 ranges	Infinite, 2 ranges	Infinite, 2 ranges
Creeper Range Available	np	No	No	np	np
<b>OPTIONAL TRANSMISSION 1</b>					
Transmission Type	No option	No option	No option	No option	No option
Number of Forward / Reverse Speeds	No option	No option	No option	No option	No option
<b>HYDRAULIC SYSTEM</b>					
Implement Pump Flow, gpm (Lpm)	4.6 (17.4)	3.5 (13.2)	6.5 (24.6)	6.2 (23.5) total	4.3 (16.5)
Number of Standard Remote Valves	np	2	1 optional	np	np
<b>3-POINT HITCH FEATURES</b>					
3-Point Hitch Category	Category 1	Limited Category 1	Category 1	Category 1	Category 1
<b>3-POINT HITCH LIFT CAPACITY</b>					
Standard Lift Capacity 24 Inches behind pin, lb (kg)	728 (330)	681 (309)	700 (318)	680 (310)	661 (300)
Standard Lift Capacity at lift pin, lb (kg)	970 (440)	1,157 (525)	np	1,210 (550)	np
<b>WHEELBASE / TRACKBASE</b>					
Wheelbase/Trackbase, MFD/4WD or Track, in (mm)	56 (1422)	57.1 (1450)	55.1 (1400)	55.1 (1400)	57.1 (1450)
<b>WEIGHT (w/TIRES OR TRACKS)</b>					
Weight, MFD/4WD w/ROPS, lb (kg)	1,433 (650)	1,345 (610)	1,485 (675)	1,443 (655)	1,433 (650)
Weight, MFD/4WD or Tracks w/Cab, without ballast, lb (kg)	No cab	No cab	No cab	No cab	No cab
<b>TIRE / TRACK SIZE</b>					
Front Tire Size or Track Width, MFD/4WD or Track	18x8.5-10 Industrial	18x8.50-10, 4PR, R4	18x8.5-10 Ag or Industrial	18x8.50-10 R1 or R4	18x8.50-10, R1, R3 or R4
Rear Tire Size or Track Width	26x12.0-12 Industrial	26x12-12, 4PR, R4	26x12.00-12 Ag or Industrial	26x12.00-12 R1 or R4	26x12.00-12, R1, R3 or R4