



Several protection screens and a “noiseless” chain tightener ensures a safe and good working environment for the user.

For sale



The unique design of the winch includes the smallest detail. The sturdy frame construction is made from special steel. A solid, wide blade/butt plate and lower pulley are standard. Chainsaw holder and trailer attachment are optional.



The PTO driven self-contained hydraulic system assures optimal performance



W-6011-EH with optional hydraulic device for unwinding wire rope, relieves the heavy work of pulling the wire out.



Two integrated storage compartments for accessories, is standard.

Technical data:	W-4011	W-6011	W-4011-EH	W-6011-EH
Pulling power	4 tons / 8.818 Lbs	6 tons / 13.228 Lbs	4 tons / 8.818 Lbs	6 tons / 13.228 Lbs
Tractor power	Ca. 40 kW	Ca. 60 kW	Ca. 40 kW	Ca. 60 kW
-3point linkage	Kat. I - II	Kat. II - III	Kat. I – II	Kat. I – II
Weight	325 kg / 716.5 Lbs	450 kg / 992 Lbs	350 kg /	475 kg /
Wire standard ø x m	9 mm x 60 m / 11/32"x196'10"	11 mm x 60 m / 7/16"x196'10"	9 mm x 60 m / 11/32"x196'10"	11 mm x 60 m / 7/16"x196'10"
Wire max. ø x m	9 mm x 80 m / 11/32"x267"	11 mm x 100 m / 7/16"x295'3"	9 mm x 80 m / 11/32"x267"	11 mm x 100 m / 7/16"x295'3"
Pulling speed v/540 rpm	0,7 - 1,8 m/s / 1,6 – 4,02 m/hr	0,5 - 1,3 m/s / 1,1 – 2,9 m/hr	0,7 – 1,8 m/s / 1,6 – 4,02 m/hr	0,5 – 1,8 m/s / 1,1 – 2,9 m/hr
PTO attachment height	45 cm / 1'5"	58 cm / 1'10"	45 cm / 1'5"	58 cm / 1'10"
Height top pulley	125 cm / 4'1"	145 cm / 4'9"	125 cm / 4'1"	145 cm / 4'9"
Total height	220 cm / 7'6"	230 cm / 7'7"	220 cm / 7'6"	230 cm / 7'7"
Dozerblade	65 x 150 cm / 2'2" x 4'11"	75 x 160 cm / 2'6" x 5'3"	65 x 150 cm / 2'2" x 4'11"	75 x 160 cm / 2'6" x 5'3"
Protective screen	Standard	Standard	Standard	Standard

Importør/forhandler:

Producent: **Fransgård**
 Fransgård Maskinfabrik A/S
 Fredbjergvej 132 DK-9640 Farsø
 www.fransgard.dk

Fransgård W- winch



- Forstline W-xx11 winches are unique in all details and are available in two sizes.
- The winch was developed and constructed in a close relation with the user.
- The brake and clutch are easily operated by pulling the nylon lines.
- Optimum security for the operator is ensured with several screens offering protection from moving parts.
- W-6011-EH can be equipped with hydraulic device for unwinding wire rope.
- A special developed "noiseless" chain pulling system ensures a good working environment.
- Optimum distance between top pulley and wire roll ensures a perfect spooling of the wire cable.
- Several compartments for storing equipment and the possibility of mounting a trailer coupling.



Fransgård

Fransgård Maskinfabrik A/S
9640 Farsø, Denmark www.fransgard.dk