

Landscape Seeder Specifications Landscape Models (5ft. & 6 ft.)

Product Attributes	LSP-5	LSP-6	LSS-6
Approximate Weight	924 lbs. (416 kg)	1,006 lbs. (453 kg)	1,242 lbs. (559 kg)
Working Width	5 ft. 0 in. (1.25 m)	6 ft. 0 in. (1.8 m)	6 ft. 0 in. (1.8 m)
Transport Width	6 ft. 0 in. (1.8 m)	7 ft. 0 in. (2.1 m)	7 ft. 0 in. (2.1 m)
Transport Height	Dependent Upon Tractor	Dependent Upon Tractor	Dependent Upon Tractor
Overall Height	3 ft. 7 in. (1.08 m)	3 ft. 7 in. (1.08 m)	3 ft. 7 in. (1.08 m)2
Overall Length	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)	2 ft. 6 in. (0.8 m)
Seed Box	All Steel Construction with Cover	All Steel Construction with Cover	All Steel Construction with Cover
Seed Box Capacity - Agitator Box	3.75 bu.	4.5 bu.	4.5 bu.
Seed Meters	Blade Agitator	Blade Agitator	Blade Agitator
Seed Meter Drive	Ground Driven	Ground Driven	Ground Driven
Seed Opening Spacing	3 in. (76.2 mm)	3 in. (76.2 mm)	3 in. (76.2 mm)
Seed Delivery	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray	Broadcast with Wind Deflector Tray
Pulverizer Roller - Front	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron	11.5 in. (292 mm) Gray Cast Iron
Pulverizer Roller - Rear	9.5 in. (241 mm) Gray Cast Iron	9.5 in. (241 mm) Gray Cast Iron	9.5 in. (241 mm) Gray Cast Iron
Pulverizer Axle Bearings	Greaseable	Greaseable	Greaseable
Pulverizer Axle Size - Front	8.625 in. (219 mm)	8.625 in. (219 mm)	8.625 in. (219 mm)
Pulverizer Axle Size - Rear	1.75 in. (44.5 mm)	1.75 in. (44.5 mm)	1.75 in. (44.5 mm)
Coil Tine Wheel Track Remover	Standard	Standard	Standard
Three-Point Hitch	Cat. I - II Free Link; Cat. I Quick Coupler Hitch	Cat. I - II Free Link; Cat. I Quick Coupler Hitch	Cat. I - II Free Link; Cat. I Quick Coupler Hitch
Cat. II Quick Coupler Hitch Adaptor Kit	Optional	Optional	Optional
Lift Sling Kit	Optional	Optional	Optional
Electronic Acre Meter Kit	Optional	Optional	Optional
Brush Agitator Kit	Optional	Optional	Optional
Turfmaker Sprockets	Optional	Optional	Optional
SMV Emblem	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard
Horsepower Requirements	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up	35 HP (26.88 kW) and up
Recommended Operating Speed	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)	3 to 5 MPH (5 to 8.3 km/h)