



4620-24 Specifications

24' Folding Seeder

Product Attributes	SS-24
Description	24 ft. (7.3 m) Agricultural Seeder
Approximate Weight (Empty)	16,178 lbs. (7,338 kg)
Working Width	24 ft. (7.3 m)
Transport Width	13 ft. 9 in. (4.2 m)
Overall Length (Transport)	31 ft. 2 in. (9.5 m)
Hitch	Semi-Mounted Two-Point Hitch
Hitch Category	Cat. II & III Free Link; Cat. II, IIIN, III Quick Coupler
Transport Tires	(4) 12.5L x 15 FI
Hydraulic Circuits Required	3
Seed Box	All Steel Construction
Seed Box Capacity	15 Bushels (528.6 l) Each Wing
Seed Metering	Micro-Meters with 6 in. (152 mm) Spacing
Seed Metering Drive	Ground Driven with Independent Electric Seeder Clutches
Pulverizer Rollers	Cast Iron with Notched Profile
Front Roller	15.75 in. (400 mm) Diameter
Rear Roller	15.75 in. (400 mm) Diameter
Pulverizer Roller Bearings	1.75 in. (45 mm) Flange Bearing
Seeder Wings	Float 5 Degrees Left to Right and 5 Degrees Front to Rear on Torsion Springs
Pivot Points	Utilize Maintenance Free Polymer Bearings
Coil Tine Track Remover	Standard
Electronic Acre Meter Kit	Standard
LED Safety Warning Lights & SMV Emblem	Standard
Powder Coat Paint, Red	Standard
Horsepower Requirements	Minimum of 150 HP (111.8 kW)
Three-Point Hitch Lift Capacity	7,500 lbs. (3,402 kg)
Recommended Operating Speed	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions