

Front Unload		RT616	RT618	RT620	RT622
DIMENSIONS					
Floor Length		16'6"	18'6"	20'6"	22'6"
Overall Length	RT/RTX600	19'8"	21'8"	23'8"	25'8"
Inside Height (without roof)	std height	6'3"	6'3"	6'3"	6'3"
	high sides	7'3"	7'3"	7'3"	7'3"
Overall Height (without roof)					
top of side	std height	94"	94"	94"	94"
	high sides	106"	106"	106"	106"
top of door pivot (RT/RTX200 only)	std height	103"	103"	103"	103"
	high sides	115"	115"	115"	115"
Less 4" truck & trailer mounts (except on XT1600 trailer*)		*	*	*	
Overall Height (with roof) - wagon mount version	std height	114.5"	114.5"	114.5"	114.5"
	high sides	126.5"	126.5"	126.5"	126.5"
Inside Width		89.5"	89.5"	89.5"	89.5"
Overall Width with conveyor extension up		109.5"	109.5"	109.5"	109.5"
Stringer Width/Height					
truck/XT2200 trailer mount		33.5"/6"	33.5"/6"	33.5"/6"	33.5"/6"
wagon mount		42"/10"	42"/10"	42"/10"	42"/10"
Capacity (struck level) cu. ft. (without roof)	(6'3") std height	769	862	956	1049
	(7'3") high sides	892	1000	1108	1217
Capacity cu. ft. (with roof)	(6'3") std height	944	1058	1174	1288
	(7'3") high sides	1067	1196	1326	1456
SPECIFICATIONS					
Front Apron Drive Shaft		2"	2"	2"	2"
Tubular Upright Spacing		24"	24"	24"	24"
All Steel Frame - 24" centers (no wood)		Std 24"	Std 24"	Std 24"	Std 24"
HD Tubular Floor Supports		2x2	2x2	2x2	2x2
HD Top Rail Formed (no side supports needed)		Std	Std	Std	Std
Commercial Grade Geardrive (no worm gears)		Std	Std	Std	Std
STANDARD FEATURES					
RT Variable Speed System - 0-17'/minute (PTO drive standard)		Std	Std	Std	Std
Apron Chains (heavy duty pintle)		667X	667X	667X	667X
Auger Feathering System & Conveyor Clutch/Safety Clutch		Std	Std	Std	Std
Cross Conveyor Chain Hold-Downs		Std	Std	Std	Std
Fold-Down Conveyor Extension with Lift Assist		Std	Std	Std	Std
OPTIONAL EQUIPMENT					
Hydraulic Front Drive System (in lieu of PTO)		Opt	Opt	Opt	Opt
Hydraulic In-Cab Controls (in lieu of PTO) - includes hyd lift conveyor		Opt	Opt	Opt	Opt
36" Fold-Down Cross Conveyor Extension (in lieu of standard 24")		Opt	Opt	Opt	Opt
Hydraulic Lift Option for Fold-Down Cross Conveyor Extension		Opt	Opt	Opt	Opt
Roof Assembly (removable)		Std	Std	Std	Std
6" Higher Roof Assembly (removable) - or 12" higher sides		Opt 616	Opt 618	Opt 620	Opt 622
Roof Hood Assembly (right hand, open top units only)		Opt	Opt	Opt	Opt
Truck Mount/Trailer Mount/Wagon Mount		Opt	Opt	Opt	Opt
Tarp Systems (with front enclosures)					
Front to Back Scissor Tarp (electric)		Opt	Opt	Opt	Opt
Side to Side Roll Tarp (electric)		Opt	Opt	Opt	Opt
Clad Tuff Fiberglass Sides & Back		Opt	Opt	Opt	Opt
Superslide, Solid Poly Floor (no plywood) (RT600)		Opt 616	Opt 618	Opt 620	Opt 622