

## Fertilizer Applicator

| MODEL                     | 1860   |
|---------------------------|--|
| Tank size                 | 1800 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill   |
| Tool bar                  | - Available in 24/30" (25), 36/20" (37), 36/22" (37), 18/38" (19) widths<br>- Active hydraulic down pressure.<br>- Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections |
| Tire size                 | Dual tire 380/90R54, 320/90R54<br>Single tire/rim 380/90R54  |
| Wheel spacing             | 60"/120", 80"/120", 88"/132", 76"/152" Duals<br>120", 132" Single tire   |
| Plumbing                  | - Ace hydraulic driven centrifugal pump kit.<br>- 5 section control valves<br>- Raven 450 rate controller  |
| Coulters                  | 20" ripple, spring-cushioned<br>Knives or injectors<br>Hydraulic depth control assist  |
| Ground clearance          | 36" in field operation, 54" on turn rows   |
| Transport width           | 18' 6"   |
| Transport height          | 13' 6"   |
| Transport length          | 24' 3"   |
| Hitch pin to axle length  | 185"   |
| Fresh water safety tank   | 9 gallon   |
| Quick fill                | 3"   |
| Empty weight <sup>1</sup> | 20,100 lb  |
| Tongue weight, transport  | 1,520 lb   |
| Tongue weight, field      | 5,380 lb   |

<sup>1</sup> Approximate measurement

| MODEL                     | 2460   |
|---------------------------|--|
| Tank size                 | 2400 US gallon tank, stainless steel baffle, hopper bottom sump w/ 3" fill   |
| Tool bar                  | - Available in 24/30" (25), 36/20" (37), 36/22" (37), 18/38" (19) widths<br>- Active hydraulic down pressure.<br>- Four (4) gauge wheels. - Double 5 x 7 mainframe with ground contour following wing sections |
| Tire size                 | Dual tire 380/90R54, 320/90R54   |
| Wheel spacing             | 60"/120", 80"/120", 88"/132", 76"/152" Duals   |
| Plumbing                  | - Ace hydraulic driven centrifugal pump kit.<br>- 5 section control valves<br>- Raven 450 rate controller  |
| Coulters                  | 20" ripple, spring-cushioned<br>Knives or injectors<br>Hydraulic depth control assist  |
| Ground clearance          | 36" in field operation, 54" on turn rows   |
| Transport width           | 18' 6"   |
| Transport height          | 13' 6"   |
| Transport length          | 24' 3"   |
| Hitch pin to axle length  | 185"   |
| Fresh water safety tank   | 9 gallon   |
| Quick fill                | 3"   |
| Empty weight <sup>1</sup> | 20,100 lb  |
| Tongue weight, transport  | 1,520 lb   |
| Tongue weight, field      | 5,380 lb   |

<sup>1</sup> Approximate measurement