

Backhoes		
MODEL		BE-BK215
DIGGING DEPTH (TWO FOOT FLAT BOTTOM)	A	7'2"
REACH FROM CENTER LINE OF SWING PIVOT	B	10'9"
LOADING HEIGHT (BUCKET AT 60°)	C	6'8"
MAXIMUM LEVELING ANGLE	D	10 °
SWING ARC	E	180 °
TRANSPORT HEIGHT (MAXIMUM)	F	6'4"
TRANSPORT OVERHANG	G	4'4"
BUCKET ROTATION	H	180 °
STABILIZER SPREAD (DOWN POSITION)	I	5'8"
STABILIZER SPREAD (UP POSITION)	J	4'4"
ANGLE OF DEPARTURE	K	21 °
SHIPPING WEIGHT		1020 LBS
BUCKET DIGGING FORCE		2600 LBS
DIPPERSTICK DIGGING FORCE		1900 LBS
OPERATING PRESSURE		2300 PSI
MIN HP		40-100HP

- 12" BUCKET INCLUDED
- WITH ITALIAN CONTROL VALVE, VERY COMFORTABLE OPERATING
- BKHYDKIT (DEALER INSTALLED OPTION ONLY)
- BKPAD
- BK8 - 8" BUCKET
- BK16 - 16" BUCKET.....
- BKSTB
- BKTHUMB - MECHANICAL THUMB

*BK215 – Remote Hydraulics

