

Backhoes		
MODEL		BE-BK175
DIGGING DEPTH (TWO FOOT FLAT BOTTOM)	A	6'4"
REACH FROM CENTER LINE OF SWING PIVOT	B	19'3"
LOADING HEIGHT (BUCKET AT 60°)	C	5'3"
MAXIMUM LEVELING ANGLE	D	10°
SWING ARC	E	180°
TRANSPORT HEIGHT (MAXIMUM)	F	6'2"
TRANSPORT OVERHANG	G	3'8"
BUCKET ROTATION	H	180°
STABILIZER SPREAD (DOWN POSITION)	I	5'8"
STABILIZER SPREAD (UP POSITION)	J	4'4"
ANGLE OF DEPARTURE	K	21°
SHIPPING WEIGHT		948 LBS
BUCKET DIGGING FORCE		2315 LBS
DIPPERSTICK DIGGING FORCE		1543 LBS
OPERATING PRESSURE		2300 PSI
MIN HP		20-50HP

- 12" BUCKET INCLUDED
- WITH ITALIAN CONTROL VALVE, VERY COMFORTABLE OPERATING
- BKHYDKIT (DEALER INSTALLED OPTION ONLY)
- BKPAD
- BK8 - 8" BUCKET
- BK16 - 16" BUCKET.....
- BKSTB
- BKTHUMB - MECHANICAL THUMB

*BK215 - Remote Hydraulics

