



4630-36 Specifications

36' Folding Seeder

Product Attributes	SSBP-36	SSP-136	SSP-2361
Description	(3) SSBP-12 Agricultural Seeders	(3) SSP-112 Agricultural Seeders	(3) SSP-2121 Agricultural Seeders
Approximate Weight (Empty)	18,440 lbs. (8,364 kg)	18,100 lbs. (8,210 kg)	20,366 lbs. (9,238 kg)
Working Width	36 ft. (10.97 m)	36 ft. (10.97 m)	36 ft. (10.97 m)
Transport Width	13 ft. 6 in. (4.1 m)	13 ft. 6 in. (4.1 m)	13 ft. 6 in. (4.1 m)
Transport Height	11 ft. (3.4 m)	11 ft. (3.4 m)	11 ft. (3.4 m)
Overall Length	31 ft. (9.4 m)	31 ft. (9.4 m)	31 ft. (9.4 m)
Hitch	Cast Single Lip Cat. IV	Cast Single Lip Cat. IV	Cast Single Lip Cat. IV
Wheels - Center Section	8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles	8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles	8 Bolt Hubs with 2 7/8 in. (73.1 mm) Slip In Spindles
Wheels - Wings	6 Bolt Hubs with 2 in. (50.8 mm) Spindles	6 Bolt Hubs with 2 in. (50.8 mm) Spindles	6 Bolt Hubs with 2 in. (50.8 mm) Spindles
Tires - Center Section	(4) 12.5L x 15, (GY-FI) Load F	(4) 12.5L x 15, (GY-FI) Load F	(4) 12.5L x 15, (GY-FI) Load F
Tires - Wings	(4) 11 L x 15, 12 Ply	(4) 11 L x 15, 12 Ply	(4) 11 L x 15, 12 Ply
Hydraulic Circuits Required	3 (+1 for Row Marker Kit)	3 (+1 for Row Marker Kit)	3 (+1 for Row Marker Kit)
Seed Box	All Steel Construction	All Steel Construction	All Steel Construction
Seed Box Capacity	15.75 Bushels (555.0 l) Front / 15.75 Bushels (555.0 l) Rear	27 Bushels (951.5 l)	69 Bushels (2,431.5 l)
Seed Metering	Standard Micro-Meter Front / Blade Agitator Rear	Standard Micro-Meter	High Capacity Micro-Meter
Seed Metering Drive	Independent Electric Seeder Clutches	Independent Electric Seeder Clutches	Independent Electric Seeder Clutches
Pulverizer Rollers	Cast Iron with Notched Profile	Cast Iron with Notched Profile	Cast Iron with Notched Profile
Front Roller (Fixed)	14.5 in. (368.3 mm) Diameter	14.5 in. (368.3 mm) Diameter	14.5 in. (368.3 mm) Diameter
Rear Roller (Independently Floating)	10.25 in. (260.4 mm) Diameter	10.25 in. (260.4 mm) Diameter	10.25 in. (260.4 mm) Diameter
Blade Agitator for Rear Seed Box	Standard	N/A	N/A
Cage Agitator for Rear Seed Box	Optional	N/A	N/A
5-Strip Brush Agitator for Rear Seed Box	Optional	N/A	N/A
Front Seed Box Divider Kit	Standard	N/A	N/A
Rear Roller Assembly with Turfmaker Sprockets	Optional	Optional	Optional
Folding Row Marker Kit	Optional	Optional	Optional
Wheel Track Removers - Wings	Standard	Standard	Standard
Coil Tine Track Remover Kit - Center Section	Standard	Standard	Standard
Front Roller Scraper Kit for One Seeder	Optional	Optional	Optional
Brillion Elite Mini Monitor	Standard	Standard	Standard
LED Safety Warning Lights & SMV Emblem	Standard	Standard	Standard
Safety Chain Kit	Standard	Standard	Standard
Powder Coat Paint, Red	Standard	Standard	Standard
Horsepower Requirements	Minimum of 200 HP (149.1 kW)	Minimum of 200 HP (149.1 kW)	Minimum of 200 HP (149.1 kW)
Recommended Operating Speed	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions	4.5 to 6.0 MPH (7.2 to 9.7 km/h) Dependent on Conditions