



6200 Series Tandem Disc Harrow Specifications

Chevron Conditioner Reel

6211 Non-Folding Models

Adapts To:	6211-12	6211-14	6211-15
Approximate Weight	1,042 lbs. (473 kg)	1,641 lbs. (744 kg)	1,673 lbs. (759 kg)
Reel Diameter	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Section Width	(1) 13 ft. 0 in. (4.0 m)	7 ft. 7 in. (2.3 m) -- 7 ft. 7 in. (2.3 m)	8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m)
Independent Hydraulic Lift	Optional	Optional	Optional

6231 Three-Section Folding Models

Adapts To:	6231-21	6231-23	6231-26	6231-29
Approximate Weight	2,084 lbs. (945 kg)	2,201 lbs. (998 kg)	2,324 lbs. (1,054 kg)	2,470 lbs. (1,120 kg)
Reel Diameter	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Section Width	6 ft. 0 in. (1.8 m) -- 10 ft. 0 in. (3.0 m) -- 6 ft. 0 in. (1.8 m)	8 ft. 0 in. (2.4 m) -- 8 ft. 0 in. (2.4 m) -- 8 ft. 0 in. (2.4 m)	10 ft. 0 in. (3.0 m) -- 8 ft. 0 in. (2.4 m) -- 10 ft. 0 in. (3.0 m)	12 ft. 0 in. (3.7 m) -- 8 ft. 0 in. (2.4 m) -- 12 ft. 0 in. (3.7 m)
Independent Hydraulic Lift	Optional	Optional	Optional	Optional

Adapts To:	6231-30	6231-33	6231-36
Approximate Weight	2,674 lbs. (1,213 kg)	2,765 lbs. (1,254 kg)	3,265 lbs. (1,481 kg)
Reel Diameter	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Section Width	9 ft. 6 in. (2.9 m) -- 13 ft. 0 in. (4.0 m) -- 9 ft. 6 in. (2.9 m)	11 ft. 0 in. (3.4 m) -- 13 ft. 0 in. (4.0 m) -- 11 ft. 0 in. (3.4 m)	13 ft. 0 in. (4.0 m) -- 13 ft. 0 in. (4.0 m) -- 13 ft. 0 in. (4.0 m)
Independent Hydraulic Lift	Optional	Optional	Optional

6250 Five-Section Folding Models

Adapts To:	6250-40	6250-45	6250-50
Approximate Weight	4,296 lbs. (1,949 kg)	4,595 lbs. (2,084 kg)	4,780 lbs. (2,168 kg)
Reel Diameter	14 in. (356 mm)	14 in. (356 mm)	14 in. (356 mm)
Rod Diameter	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)	0.875 in. (22.2 mm)
Reel Protection	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure	Individual Arm Mounted with Spring Loaded Down Pressure
Section Width	7 ft. 7 in. (2.3 m) -- 7 ft. 7 in. (2.3 m) -- 13 ft. 0 in. (4.0 m) -- 7 ft. 7 in. (2.3 m) -- 7 ft. 7 in. (2.3 m)	8 ft. 9 in. (2.7 m) -- 8 ft. 9 in. (2.7 m) -- 13 ft. 0 in. (4.0 m) -- 8 ft. 9 in. (2.7 m) -- 8 ft. 9 in. (2.7 m)	10 ft. 0 in. (3.0 m) -- 10 ft. 0 in. (3.0 m) -- 13 ft. 0 in. (4.0 m) -- 10 ft. 0 in. (3.0 m) -- 10 ft. 0 in. (3.0 m)
Independent Hydraulic Lift	Optional	Optional	Optional