



Running Gears - Wagons

SINGLE & TANDEM AXLE

10 models to choose from
8-22 Ton Capacity



**Torture tested & field proven
for your satisfaction!**

**Brand New
SRX & DRX
Models!**



**Forage Box &
Gravity Box
Applications**



Flat Rack, Tender Wagon & Industrial Applications

**DESIGNED & MANUFACTURED TO ACCOMMODATE
TODAY'S DEMANDING OPERATIONS!**

Flexibility • Strength • Refined Steering System


Farm Equipment Buyers Trust the Name *Meyer!*





Meyer has a Wagon to

SRX Series Single Reach



**HD Single,
C-Section Reach
(X & SRX Models)**



Feature a completely redesigned frame and precision steering system. They provide maximum quality trailing, a tighter turning radius and easier steering along with a host of other features.



4-Wheel Single Models:
X804W, X1004,
SRX1304, DRX1604,
DRX1704, X2004



Meyer DRX

Available in single
or tandem models from
16 – 22 ton capacity

X/SRX/DRX FEATURES: Flexibility & Strength



ALL MODELS INCLUDE Heavy Duty Adjustable Tongue Assembly. The system makes fast work of hook-ups and is adjustable to match desired length. Spring assist lift is standard! (3x5 inner tongue on 16 ton and larger models!)



Robust, 4x8" tubular **Bolsters** are standard on all models (4x10" on X2004) – not welded channel like others. (Optional 3" riser block shown above.)

1304/1506/1604/1904



SRX & DRX Models feature vertical pin contains tap on critical parts. All models



X Series Steering (X804W, X1004, X1206) feature elbow-type spindles and a strong, rear mounted steering system. (dual tie rod on 8/10 ton – single tie rod on 12 ton)



The strongest, best trailing go

Match Your Application!



Meyer SRX

Available in single and tandem models from 13 – 15 ton capacity



6-Wheel Tandem Models:

X1206, SRX1506
DRX1906, DRX2206

DRX Series Dual Reach



HD Dual,
U Channel Reaches
(DRX Models)



Bursting with new technology! A precision steering system and new frame design provide maximum quality trailing, tighter turning radius and easier steering. This is one impressive gear.

DRX Series: Dual Reach System provides added strength & stability on high capacity models



DRX1704/DRX2206



HEAVY DUTY VERTICAL KINGPIN ASSEMBLY

ure **T-Type Steering** design for strength and accuracy. The erred bearings for ease of steering while eliminating stress iving parts including tie rod pivots are greaseable!

The Meyer SRX/DRX wagons feature **fully redesigned steering** from the ground up. HD steering stops, vertical kingpin assembly with replaceable bushings, 1.5" horizontal tongue bolt and a heavy duty tie-rod arrangement provide "straight as an arrow" performance.



4 corner mounted **stake pockets** retain the load on your Meyer wagon. Most models have a bolt on system for easy replacement or riser kit installation when using large diameter tires. (SRX/DRX style pictured)



DRX2206 Tandem is outfitted with a **rear cradle frame** which distributes your load over a larger surface area for less stress. **3" riser set** standard on DRX2206.

ear you will ever own - Meyer!





Running Gears - Wagons

Dimensions • Specifications • Options

	Capacity	Weight w/ tires	Tread Width	Spindle Diameter	Hub Size	Bolster Size/ Height	Reach Size	Wheel Base	Quick Hitch Pole	Pole Adj.	Hyd. Surge Brakes
SINGLE AXLE											
X804W	8 ton	900# w/ 11L	90"	1¾"	6 bolt 3560#	4" x 8" tube 27" w/11L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	82"-100"	N/A
X1004	10 ton	1025# w/12.5L	76"	2"	6 Bolt 4570#	4" x 8" tube 28" w/12.5L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	82"-100"	N/A
SRX1304	13 ton	1,780# w/14L	83"	2¾"	8 Bolt 6000#	4" x 8" tube 31" w/14L	5" Wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	97"-115"	Optional
DRX1604	16 ton	2,085 w/16.5L	88"	2¾"	8 Bolt 8000#	4" x 8" tube 32" w/16.5L	(x2) 4" wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
DRX1704	17 ton	2,770# w/trk tires	85"	3"	8 Bolt 8000#	4" x 8" tube 34" w/Trk tires	(x2) 4" wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
X2004	20 ton	3,250# w/trk tires	86.5"	3.5"	10 Bolt 15,000#	4" x 10" tube 36.75" w/Trk Tires	5" Wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	84" - 110"	Optional
TANDEM AXLE											
X1206	12 ton	1,525# w/12.5L	76"	2"	6 Bolt 4570#	4" x 8" tube 28" w/12.5L	4" wide x 88" L Opt. 112"	93" to 141"	Standard w/ spring asst.	97"-115"	N/A
SRX1506	15 ton	2,415# w/14L	83"	2¾"	8 Bolt 6000#	4" x 8" tube 31" w/14L	5" Wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	97"-115"	Optional
DRX1906	19 ton	2,890# w/16.5L	88"	2¾"	8 Bolt 8000#	4" x 8" tube 32" w/16.5L	(x2) 4" wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional
DRX2206	22 ton	4,065# w/trk tires	85"	3"	8 Bolt 8000#	4" x 8" tube 34" w/Trk tires	(x2) 4" wide x 112"L Opt. 136"	117" to 165"	Standard w/ spring asst.	84"-110"	Optional

OPTIONS: • Safety Chain • Long Reach Pkg • Riser Kits • Rear Hitch • Surge Brake System
 *Riser packages may be required for large diameter tires depending on application.

All running gear are designed for farm use at tractor speeds to a maximum of 20 mph. Capacities apply only when equipped with properly rated tires. Meyer Mfg. reserves the right to change its products or this description at any time without notice or obligation.



BRAKE OPTIONS



TANDEM TRAILERS



See our full line of **Tandem & Tridem** trailers for maximum maneuverability & traction!

Surge Brake Packages available on all models 13 ton and larger (single axle – 2 wheel / tandem axle – 4 wheel)

Scale Packages available for certain applications.



YOUR DEALER IS:



Meyer Mfg. Corp.

Dorchester, Wisconsin 54425

Phone: 715/654-5132 • FAX: 715/654-5513 • 1-800-325-9103
 email: sales@meyermfg.com • home page: www.meyermfg.com