



Food Plot Seeder Specifications

Product Attributes	FPSB-6
Approximate Weight	1,389 lbs. (625 kg)
Working Width	6 ft. 0 in. (1.8 m)
Overall Width	6 ft. 10 in. (2.05 m)
Overall Transport Height	Dependent Upon Tractor
Overall Height (Working)	3 ft. 5 in. (1.03 m)
Overall Length	5 ft. 8 in. (1.7 m)
Disc Assembly	
Blade Spacing	7.5 in. (191 mm)
Blade Size (Main)	18 in. (457 mm) x 9 ga.
Blade Size (End)	16 in. (406 mm) x 11 ga.
Arbor Bolt	1.125 in. (28.6 mm) Square
Gang Bearings	1.125 in. (28.6 mm) Greaseable
Angle of Operation	10 or 15 Degrees
Harrow Assembly	
Tooth Bars	2
Type of Teeth	10 in. Mini S-Tines with Reversible Points
Tooth Spacing	Nominal 7.5 in. (191 mm)
Tooth Depth of Operation	0 to 3 in. (76.2 mm) in 1 in. (25.4 mm) Increments
Under Bar Clearance	11.5 in. (292 mm)
Seeder Assembly	
Seed Box Type	All Steel Construction with Cover
Seed Box Capacity	2,625 bu. Each Box
Seed Meters	Micro-Meter and Brush Agitator
Seed Meter Drive	Positive Ground Driven with Disconnect
Seed Meter / Opening Spacing	6 in. (152 mm) / 4 in. (102 mm)
Seed Delivery	Broadcast with Wind Deflector Tray
Pulverizer Assembly	
Working Width of Pulverizer	6 ft. 0 in. (1.8 m)
Pulverizer Wheels	9.5 in. (241 mm) Gray Cast Iron
Number of Wheels	31
Pulverizer Scraper	Standard
Pulverizer Axle Bearings	1.5 in. (38.1 mm) Greaseable
Axle Size	1.75 in. (44.5 mm)
Floating Hitch	Cat. I, II Free Link; Cat. I, II Quick Coupler Hitch
Micro-Meter Seed Box Kit	Standard
Brush Agitator Seed Box Kit	Standard
Coil Tine Drag	Optional
Cargo / Rock Box Kit	Optional
Posi-Drive Pulverizer Roller	Optional (In Lieu of Standard Pulverizer Assembly)
Powder Coat Paint, Red	Standard
Horsepower Requirements	35 HP (26.88 kW) and up
Recommended Operating Speed	3 to 5 MPH (5 to 8.3 km/h)