



FIELD CULTIVATOR

With the exclusive Max-Mix™ shank pattern, heavy-duty shank options, and five choices of rear finishing attachments, the 8000 Series Field Cultivator from Great Plains is equipped to create a level, weed-free seedbed that promotes moisture

conservation and seed germination. The Max-Mix shank pattern enhances fertilizer and manure incorporation, spreads residue evenly, reduces windrowing, and helps eliminate chemical streaking.



FIELD CULTIVATOR MODELS

Field Cultivator	Tillage Width	Transport Width	Transport Height	Engine H.P. Required	Weight
8323FC	23'	14'	10'	120+	7,590
8328FC	27' 9"	14'	12' 6"	145+	8,960
8332FC	32' 6"	14'	14' 9"	170+	9,800
8336FC	36'	16' 1"	14' 9"	190+	11,700
8539FC	39' 6"	15'	11' 9"	205+	12,550
8544FC	44'	15'	14'	230+	13,860
8548FC	48' 9"	15'	14'	255+	14,940
8551FC	51'	16' 10"	14'	270+	15,560
8556FC	55' 9"	16' 10"	16' 4"	295+	16,280
8560FC	60' 6"	16' 10"	16' 4"	320+	16,500

See www.greatplainsag.com for complete specifications.
 Specifications are subject to change without prior notification.
 Images may not depict current or standard production models.

3-Section Models

8323FC, 8328FC
8336FC



5-Section Models

8539FC, 8544FC, 8548FC
8551FC, 8556FC
8560FC



FEATURES & BENEFITS

TWO FRONT HITCH CHOICES

The standard, constant-level hitch is ideal for farms with relatively flat fields. The single-pole design on floating hitch models permits the machine to make tight turns. This results in less damage from interference with tractor components. For more challenging field conditions, choose the floating hitch option. It adds maintenance-free caster wheels to the front of the implement and a horizontal pivot at the base of the tongue, enhancing the unit's flexibility for consistent cultivation, regardless of terrain.



ADDITIONAL STANDARD FEATURES

- 28" minimum distance between shanks for superior trash flow
- Front gauge wheels on inner wing sections – mechanical
Standard on 32'–60' constant-level hitch models
- Front gauge wheels on inner wing sections – hydraulic
Standard on floating hitch models
- Double fold cylinders (5-section models only)
- 24½" underframe clearance
- Heat-treated ductile cast iron hitch tongue
- Single-point depth control with rephasing cylinders
- Maintenance-free 1¼" hardened pins on lift-axle pivots
- Greaseable walking beams and hubs
- Walking tandems on all sections
- Heavy-duty jack
- ISO hydraulic tips
- LED safety lighting

CHOOSE YOUR SHANK & SWEEPS

The heavy-duty K-flex shank (left) has 185 lbs. of point trip force. Spring-loaded Magnum shank (right) has 205 lbs. of point trip force. Both shank styles are available in minimum draft or flat lower sweeps. Sweep choices are either 10" or 11" with or without hard-surfacing.




NARROW TRANSPORT WIDTH

The 8000 Series Field Cultivator folds to a narrow 14' transport width on the smallest units and an amazing 16' 10" width on the 60' model.



NEW KNOCK-ON SWEEPS (Opt)

Quick-change system for installation and removal of sweeps. Once installed, change sweeps with a special tool and hammer.



MAX-MIX™ SHANK PATTERN

The Max-Mix shank design evenly spreads residue and incorporates fertilizer or manure for even distribution.

OPTIONS (see website for complete list of features & options)



4-BAR COIL TINE



3-BAR COIL TINE & REEL



4-BAR HIGH-RESIDUE SPIKE



3-BAR SPIKE & REEL



5-BAR SPIKE