



# 12' END WHEEL NO-TILL

The Great Plains 1206NT Drill has long been used by farmers and cattlemen, conservation groups like Pheasants Forever and NRCS for rental machines, and roadside contractors who need simple-to-operate, yet durable drills. This drill features

large end wheels designed for superior ground-gauging in rugged terrain. Additionally, the inline end wheels minimize sidelozing on contours and side hills, dramatically extending the life of the no-till openers.



# 12' END WHEEL NO-TILL MODEL

| 12' End Wheel No-Till Drill | Working Width | Transport Width | Transport Height | Engine H.P. Required | Row Spacing | Weight |
|-----------------------------|---------------|-----------------|------------------|----------------------|-------------|--------|
| 1206NT                      | 12'           | 15' 7"          | 6' 7"            | 75+                  | 7.5"        | 5,965  |

See [www.greatplainsag.com](http://www.greatplainsag.com) for complete specifications.



1206NT



## 06 SERIES OPENER

The 06 Series row unit utilizes the "Fluff and Plant" no-till system with an integrally-mounted coulters that cuts residue and prepares a mini seedbed for the trailing double-disc opener. Opener discs are 13.5" in diameter with 4mm-thick blades, 205 triple-lip sealed bearings, and a 1/4" opener disc lead. Our unique seed tube design and trailing flap control the seed all the way to the bottom of the seed trench where the seed stays in place.

CAPABLE  
**3 BOX 3 SEED 3 RATE**  
**3 3 3**



## ADDITIONAL STANDARD FEATURES

- Hydraulic depth stop
- Acremeter
- 2.4 bu./ft. box capacity
- 1 3/4"-wide fluted feed cups w/ powdered metal flutes
- Calibration crank
- Grease bank
- Direct link press wheel for depth control
- Heavy-duty coil springs
- Seed tubes and flaps
- Walkboard w/ steps
- Spring steel coulters mounting bars
- Weight bracket
- Pintle or clevis hitch
- LED safety lighting

\*only available by ordering through Parts

## OPTIONS (see website for complete list of features & options)



### LEAD COULTER OPTIONS

Choose between a wide 3/4" wavy blade, a 5/8" Turbo coulters blade that is aggressive and prepares a mini seedbed ahead of the opener, or a 5/16" fluted coulters blade that penetrates easily to perform minimum tillage.



### PRESS WHEEL OPTIONS

Choices include, from left, single 3"x13" double rib\* press wheels; single 3"x13" center rib press wheels; single 2"x13" smooth press wheels; 1"x12" double-V press wheels; and wedge-style press wheels that create a pinching action to close the trench.



### 4-SPEED GEARBOX

Changing seed rates is quick and effortless with these permanently lubricated, sealed gearboxes.



### END WHEEL DRIVE

Large end wheels provide excellent ground drive to the seed meters. Lockout hubs save drive components from wear.



### T-HANDLE DEPTH CONTROL

T-handles offer 18 different positions for accurate depth control.



SMALL SEEDS BOX ATTACHMENT



SECOND SEED BOX



NATIVE GRASS BOX



FERTILIZER BOX