



# NO-TILL SEEDER

The NTS25 No-Till Seeder, available in 7', 9', and 11' widths, makes quick work of renovating pastures, reclaiming rights-of-way, and planting food plots. Designed with ease of use in mind, the NTS25 Series Seeder comes with a variety of built-

in features. Metering is ground-driven by the rear packer-roller. Any of the seed boxes can easily be disengaged with simple lockout pins on each drive sprocket, or all the boxes can be locked out with one pin on the main sprocket.



# NO-TILL SEEDER MODELS

No-Till Seeder	Working Width	Transport Width	Transport Height	Engine H.P. Required	Weight
NTS2507	7' 2"	8' 1"	N/A	40-60	1,878-2,800
NTS2509	8' 4"	9' 3"	N/A	50-85	2,090-3,123
NTS2511	10' 9"	11' 7"	N/A	60-110	2,650-3,800

See [www.greatplainsag.com](http://www.greatplainsag.com) for complete specifications. Specifications are subject to change without prior notification. Images may not depict current or standard production models.

CAPABLE  
**3 BOX 3 SEED 3 RATE**  
**3 3 3**



## ADDITIONAL STANDARD FEATURES

- Straight rear roller: 11-3/8" diameter, notched, cast gray iron rings
- Dual front spiked rollers are adjustable up to 18°
- Roller spike: 1/2" x 2", heat-treated steel, replaceable
- Formed plate A-frame
- 3" x 4" tube frame
- Heavy-duty lid w/ seed splash guard
- Seed box lockouts
- Anti-reverse clutch to prevent seed cup damage
- Wide range of calibration settings
- Wind-guarded seed drop
- Lift hooks
- LED safety lighting

## OPTIONS (see website for complete list of features & options)



PULL-TYPE OPTION



NATIVE GRASS BOX




DIGITAL ACREMETER


# FEATURES & BENEFITS

## METERING COMPONENTS

All three boxes utilize the same proven metering components found in all Great Plains seeding equipment. These three metering systems allow the No-Till Seeder to plant a wide variety of crops, from the smallest clovers to the fluffiest native grasses.



Main Box



Small Seeds Box



Native Grass Box (optional)



## CHOOSE 3-POINT OR PULL-TYPE

The unique design allows the machine to be converted from a 3-point to a pull-type by adding a tongue and hydraulic gauge wheels.



## ADJUSTABLE FRONT ROLLER

Manually-adjustable front roller controls how aggressively soil is prepped for the seedbed. Run with minimum soil disturbance or set the angle for more aggressive tillage.



## 4-SPEED GEARBOX

Changing seed rates is quick and effortless with these permanently lubricated, sealed gearboxes.



## GROUND-DRIVE ROLLER

The rear packer (roller) utilizes spikes to drive the metering unit while firming seed in place.



## SMALL SEEDS BOX

Provides accurate metering of the smallest seeds.