

# 28ft Folding Stone Windrower



This Smyth built rake features a 28' raking path with a 5' windrow. Single remote hydraulics allows you to add the optional rear hitch to pull a hydraulic picker behind.

Hydraulic depth wheels with manual depth stop, lets you fine tune your working depth to suit your field conditioning and soil types.

The large 24" diameter double spiral drum with narrow hardened teeth, means you move stones not dirt without excessive soil compaction.

Automatic wing lock/unlock system, which means no lock pins required.

This unit boasts a ductile cast enclosed chaincase for extended life and durability.

Transport lighting included. With shear bolt & dual slip clutch protection, you know it's the right machine for the job!



37452 Glen's Hill Road R.R. #2 Auburn, ON Canada N0M 1E0

Ph: 519.529.7212 Fax: 519.529.3277 Email: [info@smythwelding.com](mailto:info@smythwelding.com)

[www.smythwelding.com](http://www.smythwelding.com)



# Specifications

## Structural:

- Main frame & wings 8 x 4 x .250 rectangular tube
- Wing hinge pins 2" superior shaft (on brass bushings)
- Drum axle 6-5/8" OD x .250 wall structural pipe

## Cylinders:

- Main lift cylinder - 4" x 8" with depth stop
- Wing cylinders - (2) 4" x 20"
- Wing depth cylinders - (2) 2" x 8" with depth stop

## Spindles:

- 6500 lb on main frame
- 4000 lb on wing depth

## Wheels:

- 12.5" L x 16" - 8 ply 8 bolt or optional 15" / 55-17 18 ply 8 bolt
- 11" L x 15" 8 ply 6 bolt wing depth wheel

## Driveline:

- Series #8 PTO (shear bolt) main drive - 540 RPM
- (2) Series #6 PTO (slip clutch) wing drive's

## Bearings:

- 2" bearings (ductile housing) on drum
- (1) 1-3/4", (2) 1-1/2" bearings, driveline support

