

Single Disc Salt and Sand Spreader

VSA 360 H



www.KuhnNorthAmerica.com



Invest in Quality®

PUT YOUR MIND AT EASE THIS WINTER

VERSATILE & SIMPLE

The VSA spreader is mainly intended for local municipalities, industrial sites, maintenance departments and is compatible with all small tractors. With its large range of uses, easy maintenance and durability, this spreader will ensure your peace of mind.

PRECISE SPREADING PATTERNS

A key characteristic of all KUHN spreaders is a precise spread pattern for product savings and complete coverage. This remains consistent at high speeds and application rates.

WITHSTAND EVEN THE TOUGHEST CONDITIONS

Winter conditions can be very demanding for machines. The high-quality manufacturing using many stainless-steel parts ensures a long service life.

SALT AND SAND SPREADER

VSA 360 H in brief

Models	Hopper Capacity	Spreading Width	Maximum Gross Payload
VSA 360 H	11 cu. ft. / 9 bu	2'11"-29'6" (1-9 m)	1,100 lbs (500 kg)



QUICK AND ACCURATE ADJUSTMENT

The application rate is easily adjustable, thanks to a movable stop and a precisely graduated adjustment plate. A lever controls the outlet opening and closing as necessary. If needed, application can be set only to the right or the left side.



ADAPTING TO THE PRODUCT

Easy adjustment of the outlet opening allows quick adaptation to spread different products. Stainless-steel outlets provide long life even in difficult conditions.



HOPPER WALLS

The hopper walls have steep angles to create an even flow and reduce the likelihood of material buildup.



EASY MAINTENANCE

The main components of the VSA 360 H require little maintenance and can easily be disassembled for cleaning.



CONTROLLED DISTRIBUTION

Adjustable stainless-steel deflectors provide a wide range of application widths and can be removed without tools.

VSA EQUIPMENT



1. SPECIAL AGITATOR

For non-free flowing products (sand, salt, sand-salt mix) the special agitator provides an even flow of the product toward the outlets.

2. CUSTOM-MADE CONTROLS

Several remote controls are available. Choose from 3 cable, electric or hydraulic options to suit your needs.

3. HOPPER PROTECTION

A sturdy grate, provided as standard, keeps rocks, concrete, clods and other foreign objects out to protect the bottom of the hopper.

4. SAFETY FEATURE

Road lighting is available for safe transport.

Model Specifications

	VSA 360 H
Hitch Type	3-point, Cat. 1
Hopper Capacity (cu. ft. / bu)	11/9
Maximum Gross Payload	1,100 lbs (500 kg)
Spreading Width	2'11"-29'6" (1-9 m)
Hydraulic Drive (requires 5 to 10 gpm)	Standard
Hopper Grate	Standard
Sand/Salt Agitator	Standard
Hopper Width	3'3" (1 m)
Machine Net Weight (Empty)	254 lbs (115 kg)

COMPLEMENTARY PRODUCTS

MORE PRODUCTS TO MEET YOUR NEEDS

With over 700 models of equipment, we have the most complete implement line in the industry. Whether you have a small or large operation, we have a broad range of models and options to help fit your diverse needs.



1. Offset Mowers
2. Power Tillers
3. Power Harrows
4. Fertilizer Spreaders
5. Shredders
6. Plows

For more information about your nearest KUHN dealer and other KUHN products, visit our website at www.KuhnNorthAmerica.com



Visit our YouTube channel to watch our latest product videos.



Your KUHN dealer

KUHN NORTH AMERICA, INC.

Corporate Headquarters
1501 West Seventh Avenue - Brodhead, WI 53520
Phone: (608) 897-2131 Fax: (608) 897-2561

Information given in this document is only for informational purposes and is non-contractual. Our machines are in compliance with North American safety standards. In our literature, and for improved illustration of certain details, some safety devices may not be in operating position. When operating these machines, these devices must be operated in accordance with the requirements indicated in the operator's manuals and assembly manuals. We reserve the right to change any designs, specifications or materials listed without further notice. Machines and equipment in this document can be covered by at least one patent and/or registered design. Trademarks cited in this document may be registered in one or several countries.

