

Unverferth® Seed Tenders

Seed Pro® Bulk Box Seed Tenders



Dual-Purpose **Seed Handling** **Versatility**



Models 400 and 200

Dual-purpose **Seed Handling Efficiency, Versatility**

As Mother Nature proves yearly, efficiency is your most valuable ally during planting season. The Unverferth models 400 and 200 Seed Pro® Bulk Box Seed Tenders boost your efficiency by delivering four or two 50-unit seed boxes directly to your planter or drill. You can even position the conveyor parallel to the Seed Pro Tender for transferring seed from one container to another for dual-purpose seed handling versatility.



Large collapsible canvas hopper



Heavy-duty steel hinged latches

- Easy-opening 5" x 6" doors for regulating seed flow into conveyor; dual unloading doors and chutes on model 400
- Powered by 340 cc (9.5 net HP) Honda gas engine with electric start and controls conveniently located on operating side of the unit
- 5' of hydraulically operated vertical-height adjustment for easy movement into the loading/unloading or transport positions
- Cupped and cleated belt gently carries seed at speeds up to 12 bushels per minute (6" tube with 8" belt) or 25 bushels per minute (8" tube with 12" belt available on model 400)
- Large collapsible canvas hopper at bottom of conveyor for easier filling
- Heavy-duty steel hinged latches with locks for securely fastening bulk boxes
- Undercarriage features heavy-duty steel construction, rubber-cushioned suspension and tandem axles with electric brakes on all four wheels
- LED running, hazard, brake lights and reflective striping for added transport safety



5' of hydraulically operated vertical height adjustment

5'

- Unloading chutes with steep-sloped funnel design feed conveyor from central point for fast and complete unloading efficiency
- Each compartment features self-sealing rubber funnels for channeling seed from the boxes and easy-to-attach lids for keeping the unit clean during storage
- 18' steel tube conveyor with 4'-6' telescoping downspout for total reach of 30'; optional 10' downspout reaches up to 40'
- Conveyor can be locked into position in $\frac{3}{4}$ " increments which translates to being able to position the spout at 10" increments for the greatest unloading flexibility
- Top-mounted, 6-cubic-inch hydraulic motor pulls the belt forward, keeping it tight for the most efficient seed movement and reduced motor stress
- Even weight distribution for added transport safety. Model 200 places units side-by-side for even tongue weight including when one is empty
- Standard on/off and conveyor raise/lower wired remote with magnetic mount
- Trademarked ivory and tan speckle finish provides optimum corrosion resistance to keep your investment looking new



Unloading chutes with storage lids



Standard wired remote



Options



T&G applicator

- T&G applicator for applying talc or graphite for optimum planter lubrication and more consistent seed placement
 - Automatically turns on and off in conjunction with conveyor
 - 50-lb. capacity and lower cleanout door
 - Weather-tight hopper lid keeps contents dry; gas-strut lift-assist for easy opening and filling



Internal agitation prevents bridging

- Augers material into conveyor outlet and powered by Seed Pro hydraulics
- Auger system and internal agitation provide even coating and virtually eliminates material bridging
- Includes metering control for delivering correct amount



Spare tire

- Spare tire for easily getting back on the road

Options



3-function remote

- 3- and 6-function remotes for model 400:
 - 3-function unit controls conveyor on/off; conveyor raise/lower; open/close chute doors
 - 6-function unit includes LCD display and adds engine start/stop and emergency off switch; raise/lower conveyor; conveyor swing left or right
- 2-function wireless remote for model 200 controls ON-OFF and height adjustment



6-function wireless remote

- Gooseneck hitch available for model 400 for greater towing ease; features heavy-duty jack for parking and adjustable for easily attaching to truck; or add hydraulic-operated jack for even greater parking ease
- 5th-wheel conversion for pulling with semi
- Canvas hopper cover keeps contents clean in dusty environments



Model 2410 scale package

- Model 2410 optional scale features standard operations and large LCD readout; scale monitor is enclosed in weather-tight box for verifying the quantity of seed delivered
- Light at top of spout for easier nighttime unloading



Seed Pro Bulk Box Seed Tender Specifications

Model		400	200
Overall Length (Conv. Forward)	with Bumper Hitch	22'5"	20'6"
	with Gooseneck Hitch	23'6"	—
Transport Width		8'6"	8'6"
Transport Length		18'9"	17'
Transport Height – with Boxes		11'1"	10'9"
Transport Height of Conveyor		10'10"	10'9"
Undercarriage Length		18'6"	17'
Underframe Clearance		1'1"	1'1"
Conveyor – Maximum Unloading Height		12'8"	12'4"
Conveyor – Reach at Max Height		11'3"	11'
Conveyor – Minimum Unloading Height		8'6"	8'2"
Conveyor – Reach at Min. Unloading Height		13'3"	13'
Reach with Standard 2-Stage Spout		30'(12-Row 30" Planter)	30'(12-Row 30" Planter)
Reach with Optional 3-Stage Spout		40'(16-Row 30" Planter)	40'(16-Row 30" Planter)
Appx. Empty Weight (lbs.)		5,200	3,800
Tongue Weight – Loaded (lbs.)		1,000	700
Hitch Type Std./Opt.		2-5/16" Ball/3" Pintle	2-5/16" Ball/3" Pintle
Lighting Connector		7-pin flat	7-pin flat

See your nearest Unverferth dealer today for complete details on the Seed Pro Bulk Box Seed Tenders or visit our website at umequip.com or call 1-800-322-6201.

Due to continuing improvements in the design and manufacture of all Unverferth products, all specifications contained herein are subject to change without notice.

Unverferth
Manufacturing Company, Inc.

P.O. Box 357 • Kalida, Ohio 45853
(419) 532-3121 • FAX (419) 532-2468
unverferth.com

1-800-322-6301

Please remind all family members and others to use caution and follow recommended safety practices when around all farm equipment. Unverferth Manufacturing Co., Inc., supports the efforts of Farm Safety 4 Just Kids and all other organizations that promote farm safety.

©2015 Unverferth Manufacturing Co., Inc. Printed in U.S.A.

®™ Trademarks, registered or applied for, of Unverferth Manufacturing Co., Inc., Kalida, OH.

Additional facilities in California, Georgia, Iowa, Nebraska, North Dakota, Oregon and Canada.



UMSP515110DIG