

# Tufline

## GID Series Specialty Disc

### New for for Spring of 2014!



**The design of this disc coupled with Tufline's reputation for tough dependable equipment makes this an indispensable tool for orchards and vineyards that will last for many years.**

The GID Series Specialty Disc is specifically designed for applications where narrow heavy discing is needed. It is ideal for vineyards and fruit orchards from apples to blueberries. The gangs are all independently adjustable for complete control when deep plowing to bury vegetation or light tilling to smooth and create a good seed bed for cover crop germination. Gangs can also be set to push or pull dirt as needed when discing after hoe plowing. The heavy duty cut buries and compresses cover crops to create a biomass that is beneficial to a well balanced vineyard. Orchard operators will be pleased with the ease of tilling around trees.

The mainframe is built with heavy duty 4" square tubing and has 1 1/2" square hi strength gang axles to withstand tough rocky soil found in many vineyard operations. Optional equipment includes scraper kits, a balk breaker and dirt deflectors. Notched blades are standard with smooth blades optional. The category 1 & 2 hitch is also quick hitch compatible.



Visit [www.monroetufline.com](http://www.monroetufline.com) to view the full line of Tufline implements.

Call (662) 328-8347 or email [products@monroetufline.com](mailto:products@monroetufline.com) to receive a catalog with specs and pricing.



## GID Series Standard Features

The GID Series specialty disc is designed for 50 - 85 horsepower tractors, fits category 1 & 2 hitches and is quick hitch compatible.

### Heavy Duty Mainframe

- Built with a heavy 6" X 4" square tube drawbar and 4" square tube frame.
- Axles are 1 1/2" square hi-strength steel to withstand tough rocky soil found in many vineyard and orchard operations.
- Triple sealed ball bearings

### Fully Adjustable Gangs

- The four gangs are independently adjustable to control amount and direction of soil distribution.
- Each gangs width from the center can be adjusted independently.
- Gangs have 4 choices of angle adjustments.

### Notched Disc Blades

- Notched disc blades are standard and available in two sizes; 22" X 4.5 mm, or 24" X 6 mm.

## GID Series Optional Equipment

### Smooth Disc Blades

- Smooth disc blades or a combination of smooth and notched are optional and available in two sizes; 22" dia. X 4.5 mm or 24" dia. X 6 mm.

### Scraper Kits

- Scraper kits are available and includes all mounting hardware.

### Dirt Guards

- Adjustable dirt guards are available to help protect low vines when discing.

### Balk Breaker

- A center balk breaker is available.

## Three size models available

Model #	Width of Cut	No. of Blades	Blade Spacing	Blade Dia.	Base Weight
GID V-12	55" Min. 65" max	12	9"	22" X 4.5MM, or 24" X 6MM	1,550#
GID V-14	70" Min. 80" max	14	9"	22" X 4.5MM, or 24" X 6MM	1,650#
GID V-16	70" Min. 80" max	16	9"	22" X 4.5MM, or 24" X 6MM	1,750#

