HYDRAULIC





SCM/EX/VT

Stump cutter with fixed tooth system for excavators having a weight between 12 and 20 t.

Standard equipment: flow control system valve, hydraulic hood, base plate, variable torque hydraulic piston motor, rotating plate mechanically adjustable.

Options: front fixed thumb, custom made attachment plate with pins, diverter valve.



SCM/EX/VT

Modell		Requirement		Exc. weight t.	Cutter wheel	Overal	Weight	Teeth q.ty/type
	Power HP	Flow gal/min	Pressure PSI		diameter	width		M1/M2/M3/M4
	Min - Max	Min - Max	Min - Max	Min-max	inches		lbs	
SCM/EX/VT	70 - 150	40 - 80	3200 - 5000	12 20	31	30	2248	12+12+3+3

Data refers to the machine without options.





M3

M1

High performances in a compact size

The new FAE SCM/EX/VT stump cutter is designed to meet the needs of professionals to quickly and easily remove stumps in nearly any situation.

Equipped with exclusive features, this machine ensures the best results in a compact unit.

The FAE SCM/EX/VT is supplied with a flow control system that allows it to fit different power excavators.

The front hood with hydraulic adjustment and the special front thumb guarantees very high performance and maximum safety.



Thanks to the tough, reliable and easy to use special wheel, the stumps are simply swept away.



The hydraulic adjustment of the front hood provides safer working conditions.



The front fixed thumb is designed to move the cut material.



The base plate ensures maximum safety while stationary.

The easy setting of the "flow control system" makes the SCM/EX/VT suitable for a wide power range of excavators.