

50 *Tufline* years



The Agriculture Line *Wheel Disc Series*

TW5 Tandem Wheel Disc Harrows

TW6 Tandem Wheel Disc Harrows

38 Series Offset Disc Harrows

42 Series Offset Disc Harrows

Tandem Wheel Disc Harrows

Tufline offers two series of Tandem Wheel Disc Harrows. The TW5 and TW6 Series have heavy duty mainframes designed for rugged conditions and offer a full range of options from different blades and spacing to heavy scrapers and shock flex hangers.



Offset Disc Harrows

Tufline offers its Offset Disc Harrows in three full series. The 38, and 42 series combine heavy duty manufacturing and flexible options to match almost any deep tillage requirement.



TW5 and TW6 Tandem Wheel Disc Harrows



TW5 SERIES 8' - 9' 6" Models

Tufline's TW5 Series Tandem Wheel Disc are designed for 35 to 65 horsepower tractors. The mainframe is constructed of heavy duty 3" square tube with tube type gang hangers. The gangs have a 1 1/8" square hi-strength axles with triple sealed ball bearings. All units have a front to rear leveling system and depth control. Safety chain and mounted tongue jack are standard. The units are available in 9" or 7 1/2" or combination blade spacing. 20" or 22" notched blades are standard with plain blades optional. Hydraulic cylinders, hoses, and tires are standard equipment.

Model #	Frame Width	Width of Cut	Blades	Blade Spacing	Approx. HSP	Weight
TW72420	61"	8'	24-20"	7 1/2"	35-55	1915#
TW92020	61"	8'	20-20"	9"	35-55	1805#
TW92022	61"	8'	20-22"	9"	35-55	1895#
TW972222	61"	8'	22-20"	9 - 7 1/2"	35-55	1840#
TW972222	61"	8'	22-22"	9 - 7 1/2"	35-55	1939#
TW92420	61"	9' 6"	24-20"	9"	40-65	1925#
TW92422	61"	9' 6"	24-22"	9"	40-65	2033#
TW972620	61"	9' 6"	26-20"	9 - 7 1/2"	40-65	1965#
TW972622	61"	9' 6"	26-22"	9 - 7 1/2"	40-65	2082#
TW72820	61"	9' 6"	28-20"	7 1/2"	40-65	1995#
TW72822	61"	9' 6"	28-22"	7 1/2"	40-65	2121#

TW5 SERIES 10' 6" - 15' Models

Designed for 50 to 85 horsepower tractors, these wider models have 4" X 3" and 5" X 3" hi-yield tube frames with tube type gang hangers. The gangs have a 1 1/8" square hi-strength axles with triple sealed ball bearings. All units have a front to rear leveling system and depth control. Safety chain and mounted tongue jack are standard. The units are available in 9" or 7 1/2" or combination blade spacing. 20" or 22" notched blades are standard with plain blades optional. Hydraulic cylinders, hoses, and tires are standard equipment.

Model #	Frame Width	Width of Cut	# of Bearings	Blades	Blade Spacing	Approx. HSP	Weight
TW92820	91"	10' 6"	12	28-20"	9"	50-75	2370#
TW92822	91"	10' 6"	12	28-22"	9"	50-75	2496#
TW973020	91"	10' 6"	12	30-20"	9 - 7 1/2"	50-75	2410#
TW973022	91"	10' 6"	12	30-22"	9 - 7 1/2"	50-75	2545#
TW73220	91"	10' 6"	12	32-20"	7 1/2"	50-75	2450#
TW73222	91"	10' 6"	12	32-22"	7 1/2"	50-75	2594#
TW93220	91"	12'	12	32-20"	9"	60-80	2900#
TW93222	91"	12'	12	32-22"	9"	60-80	3044#
TW973420	91"	12'	12	34-20"	9 - 7 1/2"	60-80	2950#
TW973422	91"	12'	12	34-22"	9 - 7 1/2"	60-80	3103#
TW73620	91"	12'	12	36-20"	7 1/2"	60-80	2990#
TW73622	91"	12'	12	36-22"	7 1/2"	60-80	3152#
TW93620	111"	13' 4"	16	36-20"	9"	65-85	2968#
TW93622	111"	13' 4"	16	36-22"	9"	65-85	3130#
TW74020	111"	13' 4"	16	40-20"	7 1/2"	65-85	3240#
TW74022	111"	13' 4"	16	40-22"	7 1/2"	65-85	3420#
TW973820	111"	13' 4"	16	38-20"	9 - 7 1/2"	65-85	3180#
TW973822	111"	13' 4"	16	38-22"	9 - 7 1/2"	65-85	3351#

Optional Equipment

Optional equipment is available for all TW5 Series Tandem Wheel Disc. They include:

- Heavy Duty Blade Scrapers
- Outrigger Assembly with 16" or 18" Plain Disc Blades
- Balk Breaker Assembly with Point
- Dual Wheel Kit for 10'6" to 13'4' models
- SMV Sign and Bracket
- Regreasable Bearings

Dual Wheel Models

Model #	Frame Width	Width of Cut	# of Bearings	Blades	Blade Spacing	Approx. HSP	Weight
TW74420	111"	14'	16	44-20"	7 1/2"	70-85	3340#
TW74422	111"	14'	16	44-22"	7 1/2"	70-85	3538#
TW974220	111"	14'	16	42-20"	9 - 7 1/2"	70-85	3330#
TW974222	111"	14'	16	42-22"	9 - 7 1/2"	70-85	3519#
TW94020	111"	15'	16	40-20"	9"	70-85	3390#
TW94022	111"	15'	16	40-22"	9"	70-85	3570#

Dual Wheels Optional on TW5 and 38 Series and Standard on TW6, 42 Offset Series

Optional Shock Flex Hangers

Optional Balk Breaker

Optional Outrigger

Optional Heavy Duty Scrapers

TW6 SERIES Models

Tuflin's TW6 Series Tandem Wheel Disc are designed for 60 to 160 horsepower tractors. The mainframe is constructed of heavy duty 6" X 4" and 4" X 4" square tube with tube type gang hangers. The gangs have a 1 1/2" square hi-strength gang axles with triple sealed ball bearings. All units have a front to rear leveling system and depth control. The units are available in 9" or 10 1/2" blade spacing. 22" or 24" notched blades are standard with plain blades optional. Dual wheels are standard. Safety chain and mounted tongue jack are standard. Hydraulic cylinder, hoses, and tires are standard equipment.

Optional Equipment

Optional equipment is available for all TW6 Series Tandem Wheel Disc and the TW6 Series with Shock Flex gang hangers. They include:

- Heavy Duty Blade Scrapers
- Outrigger Assembly with or 18" Plain Disc Blades
- Balk Breaker Assembly with Point
- SMV Sign and Bracket
- Regreasable Bearings

TW6 SERIES Shock Flex Models

Tuflin's TW6 Series Tandem Wheel Disc with Shock Flex gang hangers for rugged terrain are designed for 65 to 140 horsepower tractors. The mainframe is constructed of heavy duty 6" X 4" and 4" X 4" square tube with shock flex gang hangers. The gangs have a 1 1/2" square hi-strength gang axles with triple sealed ball bearings in trunion mounts. All units have a front to rear leveling system and depth control. The units are available in 9" or 10 1/2" blade spacing. 22" or 24" notched blades are standard with plain blades optional. Dual wheels are standard. Safety chain and mounted tongue jack are standard. Hydraulic cylinder, hoses, and tires are standard equipment.

Model #	Blades	# of Bearings	Spacing	Cut Width	Approx. HSP	Weight
TW6102022	20-22"	8	10 1/2"	9'	60-75	3231#
TW6102024	20-24"	8	10 1/2"	9'	60-75	3511#
TW692422	24-22"	8	9"	9' 6"	60-75	3349#
TW692424	24-24"	8	9"	9' 6"	60-75	3679#
TW692822	28-22"	8	9"	10' 6"	60-75	4065#
TW692824	28-24"	8	9"	10' 6"	60-75	4401#
TW6102422	24-22"	8	10 1/2"	10' 6"	70-85	3991#
TW6102424	24-24"	8	10 1/2"	10' 6"	70-85	4279#
TW693222	32-22"	8	9"	12'	80-90	4410#
TW693224	32-24"	8	9"	12'	80-90	4794#
TW6102822	28-22"	8	10 1/2"	12'	85-95	4260#
TW6102824	28-24"	8	10 1/2"	12'	90-110	4570#
TW693622	36-22"	12	9"	13' 4"	110-120	4726#
TW693624	36-24"	12	9"	13' 4"	110-120	5158#
TW6103222	32-22"	12	10 1/2"	13' 4"	110-120	4586#
TW6103224	32-24"	12	10 1/2"	13' 4"	110-120	4970#
TW694022	40-22"	12	9"	15'	120-140	5059#
TW694024	40-24"	12	9"	15'	120-140	5539#
TW6103622	36-22"	12	10 1/2"	15'	120-140	4887#
TW6103624	36-24"	12	10 1/2"	15'	120-140	5319#
TW694422	44-22"	16	9"	16' 8"	130-150	5409#
TW694424	44-24"	16	9"	16' 8"	130-150	5937#
TW6104022	40-22"	16	10 1/2"	17'	140-160	5630#
TW6104024	40-24"	16	10 1/2"	17'	140-160	6136#

Model #	Blades	# of Bearings	Spacing	Cut Width	Approx. HSP	Weight
TW692822SF	28-22"	8	9"	10' 6"	65-75	4533#
TW692824SF	28-24"	8	9"	10' 6"	65-75	4869#
TW6102422SF	24-22"	8	10 1/2"	10' 6"	70-85	4595#
TW6102424SF	24-24"	8	10 1/2"	10' 6"	70-85	4883#
TW693222SF	32-22"	8	9"	12'	80-90	4828#
TW693224SF	32-24"	8	9"	12'	80-90	5212#
TW6102822SF	28-22"	8	10 1/2"	12'	85-95	4550#
TW6102824SF	28-24"	8	10 1/2"	12'	85-95	4886#
TW693622SF	36-22"	12	9"	13' 4"	110-120	5144#
TW693624SF	36-24"	12	9"	13' 4"	110-120	5576#
TW6103222SF	32-22"	12	10 1/2"	13' 4"	110-120	4940#
TW6103224SF	32-24"	12	10 1/2"	13' 4"	110-120	5324#
TW694022SF	40-22"	12	9"	15'	120-140	5477#
TW694024SF	40-24"	12	9"	15'	120-140	5957#
TW6103622SF	36-22"	12	10 1/2"	15'	120-140	5305#
TW6103624SF	36-24"	12	10 1/2"	15'	120-140	5737#

38 and 42 Series Offset Disc Harrows



38 SERIES

Tuoline's 38 Series Offset Disc Harrows are designed for 50 to 90 horsepower tractors. The mainframe is constructed of heavy duty 4" square tube and 5" X 3" square tube gang beams. The gangs have a 1 1/2" RC square gang axles with triple sealed ball bearings. All units have a front to rear spring loaded leveling system and a tongue and yoke system for side draft control. Gang angle is adjustable and the gangs are available with tubular or shock flex gang hangers. 22" or 24" notched blades are standard with plain blades optional. Safety chain and mounted tongue jack are standard. Hydraulic cylinder, hoses, and tires are standard equipment.

Optional Equipment

Optional equipment is available for all 38 Offset Disc Models. They include:

- Shock Flex Hangers
- Heavy Duty Blade Scrapers
- Outrigger Assembly with 16" or 18" Plain Disc Blades
- Dual Wheel Kit
- SMV Sign and Bracket
- Regreasable Bearings

9" Blade Spacing Models

Model #	Blades	# of Bearings	Width	Approx. HSP	Tube Weight	SF Weight
38/91622	16-22"	6	6'	50	2614#	-----
38/91624	16-24"	6	6'	50	2806#	-----
38/91822	18-22"	6	6' 8"	55	2681#	2813#
38/91824	18-24"	6	6' 8"	55	2897#	3029#
38/92022	20-22"	8	7' 6"	55-60	2851#	3027#
38/92024	20-24"	8	7' 6"	55-60	3091#	3267#
38/92222	22-22"	8	8' 4"	60-65	2947#	3123#
38/92224	22-24"	8	8' 4"	60-65	3211#	3387#
38/92422	24-22"	8	9'	65-70	3044#	3220#
38/92424	24-24"	8	9'	65-70	3332#	3508#
38/92822	28-22"	8	10' 6"	75	3604#	3780#
38/92824	28-24"	8	10' 6"	75	3940#	4116#

10 1/2" Blade Spacing Models

Model #	Blades	# of Bearings	Width	Approx. HSP	Tube Weight	SF Weight
38/101422	14-22"	6	6'	50	2564#	-----
38/101424	14-24"	6	6'	50	2732#	-----
38/101622	16-22"	6	6' 10"	55	2777#	2909#
38/101624	16-24"	6	6' 10"	55	2969#	3101#
38/101822	18-22"	8	7' 8"	60	2889#	3065#
38/101824	18-24"	8	7' 8"	60	3105#	3281#
38/102022	20-22"	8	8' 6"	65	2999#	3175#
38/102024	20-24"	8	8' 6"	65	3239#	3415#
38/102222	22-22"	8	9' 4"	70	3044#	3220#
38/102224	22-24"	8	9' 4"	70	3308#	3484#
38/102422	24-22"	8	10' 2"	75	3312#	3488#
38/102424	24-24"	8	10' 2"	75	3600#	3776#



Optional Heavy Duty Scrapers

Optional Shock Flex Hangers

42 SERIES

Tufline's 42 Series Offset Disc Harrows are designed for 60 to 120 horsepower tractors. The mainframe is constructed of heavy duty 6" X 4" square tube and 6" X 4" square tube gang beams. The gangs have a 1 1/2" RC square gang axles with triple sealed ball bearings. All units have a front to rear spring loaded leveling system and a tongue and yoke system for side draft control. The gangs are adjusted by turnbuckles and or available in tubular or shock flex gang hangers. 24" or 26" notched blades are standard with plain blades optional. Dual wheels, safety chain and mounted tongue jack are standard. Hydraulic cylinders, hoses, and tires are standard equipment.

Optional Equipment

Optional equipment is available for all 42 Series Offset Disc Models. They include:

- Shock Flex Hangers
- Heavy Duty Blade Scrapers
- Outrigger Assembly with 18" or 20" Plain Disc Blades
- SMV Sign and Bracket
- Regreasable Bearings

9" Blade Spacing Models

Model #	Blades	# of Bearings	Width	Approx. HSP	Tube Weight	SF Weight
42/91824	18-24"	8	6' 8"	65	3811#	3907#
42/91826	18-26"	8	6' 8"	65	3942#	4038#
42/92024	20-24"	8	7' 6"	75	3904#	4000#
42/92026	20-26"	8	7' 6"	75	4070#	4166#
42/92224	22-24"	8	8' 4"	85-90	4154#	4250#
42/92226	22-26"	8	8' 4"	85-90	4300#	4396#
42/92424	24-24"	8	9'	95	4444#	4540#
42/92426	24-26"	8	9'	95	4576#	4672#
42/92824	28-24"	8	10' 6"	100	4724#	4868#
42/92826	28-26"	8	10' 6"	100	4903#	5047#
42/93224	32-24"	12	12'	110	5016#	5161#
42/93226	32-26"	12	12'	110	5200#	5344#
42/93624	36-24"	12	13' 6"	120	5143#	5311#
42/93626	36-26"	12	13' 6"	120	5487#	5655#

10 1/2" Blade Spacing Models

Model #	Blades	# of Bearings	Width	Approx. HSP	Tube Weight	SF Weight
42/101824	18-24"	8	7' 8"	80-85	3906#	4002#
42/101826	18-26"	8	7' 8"	80-85	3995#	4091#
42/102024	20-24"	8	8' 6"	90-95	4132#	4228#
42/102026	20-26"	8	8' 6"	90-95	4264#	4360#
42/102224	22-24"	8	9' 4"	95-100	4298#	4394#
42/102226	22-26"	8	9' 4"	95-100	4430#	4526#
42/102424	24-24"	8	10' 2"	100	4541#	4649#
42/102426	24-26"	8	10' 2"	100	4699#	4807#
42/102824	28-24"	12	11' 10"	110-115	5020#	5164#
42/102826	28-26"	12	11' 10"	110-115	5525#	5394#
42/103224	32-24"	12	13' 6"	120	5134#	5278#
42/103226	32-26"	12	13' 6"	120	5356#	5500#



The Agriculture Line



The Landscape Line



The Sportsman Line

50 Tuftline *years*

Well Built, Performance Driven Implements

To see our full line of Agricultural, Landscape and Sportsman implements visit us on the web at
monroetuftline.com

PO Box 7755, Columbus, MS 39705 • Phone (662) 328-8347 • Fax (662) 328-8361