

# 900 & 1400 HAY HIKER

## LARGE ROUND BALE CARRIER

Model	900	1400
Length	29' 8 1/2" (9.06 m)	44' 10" (13.67 m)
Width Unloaded	Rails Out - 13' 9" (4.19 m)	Rails Out - 13' 1" (3.99 m)
	Rails In - 13' 4" (4.06 m)	Rails In - 11' 4" (3.45 m)
Weight Unloaded	5,377 lbs. (2,439 kg)	7,455 lbs. (3,389 kg)
Weight Loaded	19,000 lbs. (8,618 kg)	36,455 lbs. (16,571 kg)
Load Capacity Weight	13,623 lbs. (6,179 kg)	29,000 lbs. (13,182 kg)
Load Capacity (Round Bales)	12 - 48" (1.22 m) Length	18 - 48" (1.22 m) Length
	8 - 60" (1.52 m) Length	14 - 60" (1.52 m) Length
	8 - 63" (1.60 m) Length	14 - 63" (1.60 m) Length
	8 - 72" (1.83 m) Length	12 - 72" (1.83 m) Length
Tires	(4) - 11L x 15FI - Load Range F 8 Bolt Hub	(8) - 11L x 15FI - Load Range F 8 Bolt Hub
Transport Height	8' (2.44 m)	12' (3.66 m)
Number of Wheels	4	8
Automatic Bale Turner	Standard	Standard
Automatic Bale Unloading	Standard	Standard
Frame - Tubing	2" (5 cm) x 8" (20.3 cm)	8" (20.3 cm) x 8" (20.3 cm)
Bale Divider	Standard	Standard
Bale Stop	Standard	Standard
Side Rail Kit	Standard	Standard
Cylinders - Fork - Bed Lift	(2) - 3 1/2" (8.9 cm) x 8" (20.3 cm) (1) 3" (7.6 cm) x 12" (30.5 cm)	(2) - 3 1/2" (8.9 cm) x 12" (30.5 cm) (2) 3" (7.6 cm) x 12" (30.5 cm)
Selector Valve	Standard	Standard
Safety Lights	Standard	Standard
Safety Chain	Standard	Standard
Hitch Clevis	Standard - Single Tab Optional - Double Tab	Standard - Single Tab
Tractor Requirement	120 HP (88 kW) Minimum (Two Hydraulic Remotes)	180 HP (133 kW) Minimum (Two Hydraulic Remotes)

Individual Bale Weights		
Bale Size	900	1400
48" (1.22 m)	12 @ 1135 lbs. (514 kg)	18 @ 1610 lbs. (732 kg)
60" (1.52 m)	8 @ 1700 lbs. (771 kg)	14 @ 2070 lbs. (941 kg)
63" (1.60 m)	8 @ 1700 lbs. (771 kg)	14 @ 2070 lbs. (941 kg)
72" (1.83 m)	8 @ 1700 lbs. (771 kg)	12 @ 2420 lbs. (1,100 kg)

