



AGGRESSIVE WHEN NEEDED. EFFECTIVE ALWAYS.

Wet years or dry. On pastureland or harvested field. The Rite Way RH9200 Rotary Harrow becomes the tillage equipment you need it to be by simply adjusting the tine angle from your tractor cab.

SPECIFICATIONS:

RH9200				
MODEL	DESCRIPTION	SIZE*	TRANSPORT WIDTH**	WEIGHT
RH-9245	5 Section Hydraulic Angle 25° - 40°	45' (13.72 m)	14' 6" (4.4 m)	10,950 lbs (4,967 kg)
RH-9260	7 Section Hydraulic Angle 25° - 40°	60' (18.28 m)	14' 6" (4.4 m)	13,450 lbs (6,101 kg)
RH-9275	9 Section Hydraulic Angle 25° - 40°	75' (22.86 m)	14' 6" (4.4 m)	15,950 lbs (7,235 kg)

*Size of machine is measured at maximum gang angle

**Centre section can be repositioned allowing a 12' 6" transport width

TIRES		
MODEL	MAIN FRAME	WING AXLE
All Models	16.5L x 16.1 - 8 ply	11L x 15 - 8 ply

Quick-tension adjustment tines:

11' Section - 172 tines

3/4" x 18" (1.9 cm x 45.6 cm) interlocking tines

Large floatation tires on Main Frame and Wings

FEATURES:

Auto-fold with Rite Way hydraulic pivot wheel system

Light Package



We are continuously improving our products. Design, specifications, and material are subject to change without notice.

For more information on the Rotary Harrow, or other land improvement equipment, visit your local Rite Way equipment dealer, or visit www.RiteWayMfg.com

Toll free: 1-800-352-8822



/RiteWayMfg



@RiteWayMfgCo

© RITE WAY MFG. CO. LTD. PRINTED IN CANADA 1811

