

# PROFESSIONAL SERIES



## BILLIONS OF SNOWFLAKES VS. ONE MACHINE. SEEMS ABOUT RIGHT.

They tame the wildest of snowstorms with ease. The deepest, heaviest snowfalls are given their last rites the moment you fire up this 420cc engine. You don't need to be a professional to own one, just the desire to move as much snow in as little time as possible. Go ahead, upgrade your amateur status and throw like the pros.

My dad had an Ariens, which he gave me when he upgraded his. That was about 20 years ago.

— William R.  
Bloomsburg, PA

### AUTO-TURN™ STEERING

Effortless, zero-degree turning radius.

### HYDROSTATIC TRANSMISSION AVAILABLE

Allows for infinite speed control while operating the machine.

### SKID SHOES

Commercial-grade skid shoes provide long-lasting performance that holds up to constant use.

### SUPER HIGH OUTPUT IMPELLER (SHO)

Move through heavy, wet snow with ease with our exclusive SHO technology.

### DUAL-BELT DRIVE

Exclusive to Ariens, delivers maximum power through tough conditions, plus extended belt life.

### HAND WARMERS

Stay warm and comfortable with our premium hand warmers.

### ELECTRIC CHUTE CONTROL AVAILABLE

A convenient thumb-controlled joystick makes chute turns quick and effortless with full rotations taking only 1.5 seconds.

### EFI ENGINE AVAILABLE

Our Electronic Fuel Injection Engine is easy starting, less maintenance, improved efficiency making it ideal for high altitude snow removal.

**3** YEAR  
LTD. RESIDENTIAL  
WARRANTY

**90** DAY  
LTD. COMMERCIAL  
WARRANTY

# PRODUCT SPECIFICATIONS

**RAPIDTRAK**

**RAPIDTRAK**

DESIGNATION	PROFESSIONAL 28	PROFESSIONAL 28 HYDRO EFI ALPINE EDITION™	PROFESSIONAL 32	PROFESSIONAL 32 HYDRO EFI MOUNTAINEERING EDITION™	PROFESSIONAL 36 HYDRO EFI
MODEL #	926083	926091	926082	926521	926081
STAGE TYPE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE	TWO STAGE
ENGINE POWER	420CC (21 FT/LBS)	420CC EFI (21 FT/LBS)	420CC (21 FT/LBS)	420CC EFI (21 FT/LBS)	420CC EFI (21 FT/LBS)
ENGINE BRAND	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX	ARIENS AX
STARTING SYSTEM	120V/RECOIL	120V/RECOIL	120V/RECOIL	12V KEY START/ RECOIL	120V/RECOIL
CLEARING WIDTH	28 IN (71.2 CM)	28 IN (71.2 CM)	32 IN (81.3 CM)	32 IN (81.3 CM)	36 IN (91.4 CM)
HOUSING HEIGHT	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)	23.5 IN (59.7 CM)
THROWING DISTANCE	3 - 60 FT (9-18.2 M)	3 - 60 FT (9-18.2 M)	3 - 60 FT (9-18.2 M)	3 - 60 FT (9-18.2 M)	3 - 60 FT (9-18.2 M)
CHUTE TURNING RADIUS	200°	200°	200°	200°	200°
CHUTE ROTATION	QUICK TURN™	ELECTRIC JOYSTICK	QUICK TURN	ELECTRIC JOYSTICK	QUICK TURN
DEFLECTOR CONTROL	REMOTE	ELECTRIC	REMOTE	ELECTRIC	REMOTE
HEADLIGHT	LED	LED	LED	LED	LED
TIRE SIZE	16 X 4.8 IN (41 X 12 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 6.5 IN (41 X 17 CM)	5.5 IN WIDE TRACK (14 CM)	16 X 6.5 IN (41 X 17 CM)
TIRE TYPE	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD	DIRECTIONAL SNOW TRACK	DIRECTIONAL SNOW TREAD
STEERING	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN	AUTO-TURN
DRIVE TYPE	DISC-O-MATIC	HYDROSTATIC	DISC-O-MATIC	HYDROSTATIC	HYDROSTATIC
SPEEDS	6 FORWARD 2 REVERSE	VARIABLE	6 FORWARD 2 REVERSE	VARIABLE	VARIABLE
GEAR CASE	CAST IRON	CAST IRON	CAST IRON	CAST IRON	CAST IRON
GEAR CASE WARRANTY	5YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 5YR COMM	5YR RES, 5YR COMM
IMPELLER PROFILE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE	STEEL 3 BLADE
IMPELLER DIAMETER	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)	14 IN (35.6 CM)
AUGER DIAMETER	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)	16 IN (40.6 CM)
AUGER TYPE	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED	STEEL SERRATED
SKID SHOES	COMM SKIDS	COMM SKIDS	COMM SKIDS	COMM SKIDS	COMM SKIDS
SCRAPER BAR	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE	STEEL ADJUSTABLE
PRODUCT WARRANTY	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM	3YR RES, 1YR COMM
LENGTH	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)	60.3 IN (153.2 CM)
WIDTH	30.2 IN (76.7 CM)	30.2 IN (76.7 CM)	34.2 IN (86.9 CM)	34.2 IN (76.7 CM)	38.2 IN (97.0 CM)
HEIGHT	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)	46.6 IN (118.4 CM)
WEIGHT	339.1 LBS (153.8 KG)	339 LBS (153.7 KG)	333.6 LBS (151.3 KG)	345 LBS (156.4 KG)	351.6 LBS (159.4 KG)
ACCESSORIES AT A GLANCE	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER	TIRE CHAINS, TRACK DRIVE CONVERSION KIT, FRONT WEIGHT KIT, NON-ABRASIVE SKID SHOES, SNO-THRO CAB, SNO-THRO COVER



Registered trademark and ™ trademark of AriensCo. Kawasaki®, Kohler® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit [Ariens.com](http://Ariens.com) for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary. © Copyright 2021 AriensCo. All rights reserved. 0921

VISIT [ARIENS.COM](http://ARIENS.COM) FOR DETAILS

AN **ARIENS|CO** BRAND