

**GRAVELY**

**ZT**



## GIVE YOUR LAWN THE BIG ACREAGE TREATMENT.

The Gravelly ZT brings commercial features and construction to a residential compact design. This is a comfortable, durable zero-turn mower that gives you the maneuverability you need to finish the job quickly – without sacrificing a beautifully cut lawn.

**2YR**  
TWO YEAR OR 150 HOUR  
WARRANTY

**34"**

**MODEL - 915288**

18 HP / Kawasaki® FR600V  
V-TWIN Engine

**42"**

**MODEL - 915289**

18 HP / Kawasaki® FR600V  
V-TWIN Engine

**52"**

**MODEL - 915290**

21.5 HP / Kawasaki® FR651V  
V-TWIN Engine

**A USER-FRIENDLY DESIGN** Faster than mowing with a walk-behind and easier to drive than a tractor, this compact mower is built on a robust frame and is perfect for small and medium yards. It's easy to maneuver around obstacles and the control panel is designed for ease of use with everything within reach.

**POWERFUL ENGINES** Equipped with a Kawasaki® 18 HP or 21.5 HP engine, depending on the model's deck size.

**HYDRO-GEAR® SERVICEABLE EZT® TRANSAXLES** Serviceable transaxles have optimized cooling to ensure smooth running for years of service. Integrated service ports on the internal reservoirs make maintenance easy.

**42", 52" FABRICATED DECKS** Inspired by the design of commercial decks, these 11-gauge fabricated decks are durable and affordable.

**34" STAMPED DECK** Sized to fit through standard gates and strong enough to handle medium-sized lawns with ease.

**16" HIGH BACK SEAT** A comfortable seat feels as good as it looks with natural airflow to enhance operator comfort.

**WIDE REAR TIRES** Three different ZT models each offer a different width, delivering a smooth ride and superior traction. The wider the tire, the less turf tear.

**7-POSITION HEIGHT OF CUT** A foot operated deck lift system makes cutting height adjustments a breeze. Hand lever can adjust the deck in ½" increments.



See your professional Gravelly® dealer for complete warranty details.

	34	42	52
<b>MODEL NUMBER</b>	<b>915288</b>	<b>915289</b>	<b>915290</b>
<b>ENGINE</b>	KAWASAKI® FR600V		KAWASAKI® FR651V
<b>HORSEPOWER</b>	18 HP		21.5 HP
<b>DISPLACEMENT</b>	603 CC		726 CC
<b>DRIVE SYSTEM</b>	HYDRO-GEAR® SERVICEABLE EZT® TRANSAXLES		
<b>FUEL CAPACITY</b>	2 GAL.		
<b>GROUND SPEED (APPROX. Mph)</b> <i>(Forward/Reverse)</i>	6 MPH / 3 MPH		
<b>STARTER</b>	ELECTRIC		
<b>DECK</b>			
<b>DECK MATERIAL</b>	12 GA	11 GA	
<b>DECK CONSTRUCTION</b>	STAMPED	FABRICATED	
<b>NUMBER OF SPINDLES</b>	2		3
<b>BLADE TIP SPEED (FPM)</b>	18,179	17,126	16,977
<b>SPINDLE HOUSING MATERIAL</b>	STEEL	FORGED ALUMINUM	
<b>SPINDLE SHAFT</b>	STEEL		
<b>SPINDLE BEARINGS</b>	BALL BEARING		
<b>DECK ENGAGEMENT</b>	ELECTRIC WARNER		
<b>DECK LIFT SYSTEM</b>	FOOT OPERATED		
<b>CUTTING WIDTH</b>	34 IN	42 IN	52 IN
<b>CUTTING HEIGHTS</b>	1.5 - 4.5 IN		
<b>CUTTING POSITIONS</b>	7		
<b>WHEELS</b>			
<b>FRONT</b>	11 X 4-5 PNEUMATIC		
<b>REAR</b>	18 X 6.50-8 TURF	18 X 8.50 - 8 TURF	18 X 9.50-8 TURF
<b>FEATURES</b>			
<b>SEAT</b>	HIGH BACK W/KNOB ADJUST		
<b>MACHINE</b>			
<b>HOURLY METER</b>	STANDARD		
<b>WEIGHT</b>	445 LBS	498 LBS	551 LBS
<b>LENGTH</b>	68 IN		
<b>WIDTH (w/o CHUTE)</b>	41.8 IN	46.3 IN	55.4 IN
<b>WIDTH (w/ CHUTE)</b>	44.8 IN	54.8 IN	64.2 IN
<b>HEIGHT</b>	40.2 IN		
<b>WARRANTY</b>			
<b>UNIT</b>	2 YEAR / 150 HOUR COMMERCIAL		

**ATTACHMENTS & ACCESSORIES**

- NON-POWERED BAGGER
- MULCH KITS
- ARMREST KIT
- LED LIGHT KIT
- TRAILER HITCH
- BRANDED MOWER COVER
- SEAT COVER



GRAVELLY.COM

AN ARIENS|CO BRAND

© Copyright 2023 AriensCo. All rights reserved. Registered trademark and ™ trademark of Ariens Company, Briggs & Stratton®, Kohler®, Kawasaki®, Subaru®, Yamaha® and Hydro-Gear® are registered trademarks of their respective companies. The engine horsepower information is provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower will be less. Visit gravelly.com for a complete listing of engine manufacturer power rating information. Product features and specifications subject to change without notice. Photos are a representation of the product; actual product may vary.