

# D220x300 S3 NAVIGATOR®

## HORIZONTAL DIRECTIONAL DRILL



**COMPACT FOOTPRINT.** The compact footprint of the D220x300 S3 is suited for hard-to-access, narrow jobsites, while its self-contained design lessens the need for cumbersome support equipment.



**WISE.** The sliding vise moves 35.4" (89.9 cm) to help operators position the vise for maximum efficiency when reaming or pulling product.



**COMMON CONTROLS.** The D220x300 S3 shares common controls with other drills in the Navigator lineup, which can decrease operator training time and allow faster startups.



**KNUCKLEBOOM CRANE.** The optional knuckleboom crane mounted on either side of the base anchor maneuvers heavy tooling, reducing the need for support equipment.



**POWER-TO-SIZE RATIO.** The power-to-size ratio allows for twice the pullback and rotation of similarly sized drills for versatile applications.



**ROD LOADER.** A single row, sliding arm rod loader allows for the staging of five rods at one time, increasing boring efficiency by minimizing rod loading time.

# D220x300 S3 NAVIGATOR® HORIZONTAL DIRECTIONAL DRILL

## GENERAL DIMENSIONS AND WEIGHTS

Min transport length: 39.6' (12.1 m)

Min transport width: 100" (254 cm)

Min transport height: 11.3' (3.4 m)

Weight: 78,500 lbs (35,607 kg)

## ENGINE

Make and model: Caterpillar C13 ACERT Tier 4 Final (EU Stage V)

Fuel type: Ultra-low sulfur diesel

Max engine rpm: 2100 rpm

Gross horsepower: 415 hp (309 kW)

Cooling method: Liquid

Aspiration: Turbocharged and after-cooled

EPA certification family: Tier 4 Final (EU Stage V)

## OPERATIONAL

Thrust/Pullback: 242,100 lb (1076.9 kN)

Max carriage speed at max engine rpm: 120 ft/min (36.6 m/min)

Max spindle torque (low at max engine rpm): 30,750 ft-lb (41,691.5 Nm)

Max spindle speed at max engine rpm: 180 rpm

Max ground drive speed at max engine rpm: 2.4 mph (3.9 km/h)

Noise level at operator's ear: 115 dB(A)

Drill rack angle: 10 - 17°

## FLUID CAPACITIES

Fuel tank: 134 gal (507.3 L)

Hydraulic tank: 166 gal (628.4 L)

## DRILLING FLUID SYSTEM

Make and model: Weatherford

Max flow: 350 gpm (1323 lpm)

Max pressure: 1200 psi (8.3 MPa)

## OPTIONAL CRANE

Weight: 2900 lbs (1315 kg)

Max reach: 26.3' (8 m)

Max lifting capacity: 4740 lb (2150 kg)

Max lifting capacity at max reach: 66,410 ft-lb (90,039.9 Nm)

Rotation: 360°

Wireless remote: Yes

## FEATURES

Breakout system: Open-top, dual clamp, 10.2" (25.9 cm) diameter opening

Drilling lights: Yes

Flow indicator: Yes

Cab: Yes

Strike alert: Yes

Remote lockout: Yes

## DRILL PIPE

Thread type: NC50 DS [4.5" (11.4 cm) IF double shoulder]

Length: 20.3' (6.2 m)

Rod diameter: 5" (12.7 cm) at 19.5 lb/ft

Wall thickness: .362" (9.2 mm)

Joint inside diameter: 3.5" (8.9 cm)

Joint outside diameter: 6.6" (16.8 cm)

Weight per joint: 530 lb (240.4 kg)

**NOTES:**

---

---

---

---

---

---

---

---

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Navigator and InSite are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries. CAT is a trademark of Caterpillar Inc. Weatherford is a trademark of Weatherford Technology Holdings, LLC. © 2022 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

