

ATHENS

MODEL 52



"WE PLOW THE EARTH"

The Athens Model 52 is the perfect choice for compact tractor owners, gardeners, weekenders, and small wildlife food plots. This lift-type tandem disc harrow is available in 6' 6", 7' 0", 7' 11", and 8' 2" widths and its compact design allows for easy lifting, straight pulling, and excellent maneuverability.

www.athensplowcompany.com

MODEL 52 SPECIFICATIONS

WIDTH OF CUT	NUMBER OF DISCS	DISC SPACING		NUMBER OF BEARINGS	*APPROX HP	APPROX WEIGHT (lbs.)
		FRONT	REAR			
6' 6"	16	9"	9"	8	35 - 40	868
7' 0"	18	9"	7 ½"	8	40 - 45	938
	20	7 ½"	7 ½"			
7' 11"	20	9"	9"	8	45 - 50	982
8' 2"	22	9"	7 ½"	8	45 - 55	1021
	24	7 ½"	7 ½"			

*Approximate Horse Power (HP) is only a guide. Extremely hard, soft, or boggy conditions will change these figures.

STANDARD EQUIPMENT

- Disc Blades, 18" or 20" Diameter
- Relube Quadriseal Ball Bearings
- 1 1/8" Square Cold Rolled Axle
- Spacing, 9", 7 ½", or 9" Front & 7 ½" Rear
- Adjustable Angle of Cut: 15° or 18°
- Gang Wrench
- Cat. I Hitch Free Link

OPTIONAL EQUIPMENT

- Scrapers
- Cover Discs
- Cat. II Hitch Free Link

DISC BLADES

Available in 18" and 20" diameter sizes. Choose between Smooth or Cutout. Smooth Blades are best utilized in normal field conditions. They are more economical, last longer, weigh more, and wear more evenly, thus staying sharper longer. Cutout blades are more aggressive and trap residue better than smooth blades.



FEATURES

The Main Frame is constructed of ¼" thick steel tubing and ½" thick angle which is truss-braced and reinforced to resist twisting and bending. Compact design allows for easy lifting, straight pulling, and excellent maneuverability in small fields and around close obstacles.

Axles are made from 1 1/8" square cold rolled steel to insure straightness and to keep bearings and disc in alignment.

Gang Frames are constructed from 3 x 3 x ¼" structural steel tubing.

Flangette Ball Bearings on the 52 are greaseable and have triple lip seals.

Angle of Cut adjustments can be made from 15° to 18° depending on your need for penetration and aggression.



Athens Plow Co., Inc. guarantees each piece of equipment against defective materials and workmanship for a period of one year from the date of delivery to the purchaser unless otherwise specified. Athens Plow Co., Inc. reserves the right to make changes and/or improvements in design and construction of parts or machines without notice or obligation.

Athens Plow Company, Inc. • PO Box 609 • Athens, TN 37371-0609