

SRR SERIES

manual transport conversion



SRR-15M

Mechanical version. Driven with a driveshaft connected to the tractor's PTO.



SRR-15T

Independent hydraulic system. The auxiliary pump is driven with a driveshaft connected to the tractor's PTO. The rake is provided with a reservoir and an oil cooler. The oil from the tractor does not flow into the rake's system.



SRR-15H

Fully hydraulic. The rake is driven by the tractor's hydraulic system. There is no hookup to the PTO. The tractor's oil circulates in the rake's system. The tractor must provide between 16 gpm and 32 gpm @ 3000 psi.



The SRR-15 is designed to adapt to 65-125 HP (49-93 KW) tractors. It digs and moves rocks and roots to form a windrow making them easy to pick up. Available in 3 versions.

Equipment Specifications:

Tires: 11L/15

Hookup: Pull type

Drop Box: Chain, gears and bearings in sealed oil bath

Protection: Slip clutch or pressure relief for hydraulic drive

Tooth Type: RT-400 steel replaceable and reversible, 4x stronger than regular steel

Working Width: 13' (4 m)

Transport Conversion : Manual

Other:

- Width of transport 8' (2.43 m)
- Multiple guards
- Flotation system



SRR Series

MODEL	WIDTH ft / m	WEIGHT lb / kg	RECOM. HP HP / KW
SRR-15M	15.8 / 4.8	4275 / 1940	65-125 / 48-93
SRR-15T	15.8 / 4.8	4775 / 2170	65-125 / 48-93
SRR-15H	15.8 / 4.8	4275 / 1940	65-125 / 48-93