

SWD SERIES

hydraulic transport conversion



The SWD -15 is designed to adapt to 65-125 HP (48-93 KW) tractors. It digs and moves rocks and roots to form a windrow making them easy to pick up. It is offered in 3 versions.

Equipment Specifications:

Tires: 11L/15

Hookup: Pull type

Drop Box: Chain, gears and bearings in sealed oil bath

Protection: Slip clutch (or pressure relief for hydraulic drive)

Tooth Type: RT-400 steel replaceable and reversible, 4x stronger than regular steel

Working Width: 13' 10" (4.2 m)

Transport Conversion : Hydraulic

Other:

- Width of transport 8' (2.43 m).
- Multiple guards
- Flotation system



SWD-15M



Mechanical version. Driven with a driveshaft connected to the tractor's PTO.

SWD-15T



Independent hydraulic system. The auxiliary pump is driven with a driveshaft connected to the tractor's PTO. The rake is provided with a reservoir and an oil cooler. The oil from the tractor does not flow into the rake's system.

SWD-15H



Fully hydraulic. The rake is driven by the tractor's hydraulic system. There is no hookup to the PTO. The tractor's oil circulates in the rake's system. The tractor must provide between 16 gpm and 32 gpm @ 3000 psi.

SWD Series

MODEL	WIDTH ft / m	WEIGHT lb / kg	RECOM. HP HP / KW
SWD-15M	16.7 / 5.1	4500 / 2040	65-125 / 48-93
SWD-15T	16.7 / 5.1	5000 / 2273	65-125 / 48-93
SWD-15H	16.7 / 5.1	4500 / 2040	65-125 / 48-93