



# WD SERIES

Hydraulic models, 25° swivel  
front or rear mounted



Rear installation



The WD-10H rock rake is powered directly by the tractor's hydraulic system.

It can be installed in front on a SKID STEER loader, or front or rear mounted on a 3 point hitch.

This rock rake has a 25 degree hydraulic swivel, enabling it to be perpendicular to the tractor if desired.

The tractor's hydraulic system requirements are a flow between 10 and 16 GPM (37.85 to 6-.56 l/m), with a maximum pressure of 3000 psi (207 bars).

**Equipment Specifications:**

**Tires:** 18.5" x 8.5" (470 x 206 mm)

**Hookup:** SKID STEER or 3 point hitch

**Drop Box:** Chain, gears and bearings in sealed oil bath

**Protection:** Pressure relief valve

**Tooth Type:** RT-400 steel replaceable and reversible

**Working Width:** 10' (3.05 m)

**WD Series (hydraulic drive, 25° swivel)**

MODEL	WIDTH ft / m	WEIGHT lb / kg	RECOM. HP HP / KW
WD-10H	11.4 / 3.47	2100 / 953	65+ / 49+

**Attachment Type**

3 POINT HITCH

SKID STEER

**Assembly Options**

PARTIALLY ASSEMBLED

FRONT OR REAR MOUNTED ASSEMBLY

Front installation



on SKID STEER

