



2100 Series Coulter Chisel Specifications

Chopper Attachment

Adapts To:	2112-9	2112-11	2112-13	2112-15	2132-17	2132-19	2132-21	2132-23	2132-25
Approximate Weight	1,394 lbs. (632 kg)	1,754 lbs. (796 kg)	1,930 lbs. (875 kg)	2,390 lbs. (1,084 kg)	2,992 lbs. (1,357 kg)	3,344 lbs. (1,517 kg)	3,696 lbs. (1,676 kg)	4,048 lbs. (1,836 kg)	4,358 lbs. (1,977 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Blades	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled	0.281 in. x 4 in. (7.1 x 102 mm) Beveled
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Reel Protection	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
Number of Reels	2	2	2	2	3	3	3	3	3
Independent Hydraulic Lift	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional	Optional
Weight Kit Required	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed