



# 2100 Series Coulter Chisel Specifications

## Combo Tine and Chopper Attachment

Adapts To:	2112-9	2112-11	2112-13	2112-15	2132-17	2132-19	2132-21	2132-23	2132-25
<b>Approximate Weight</b>	2,940 lbs. (1,333 kg)	3,382 lbs. (1,534 kg)	3,558 lbs. (1,614 kg)	3,624 lbs. (1,644 kg)	4,660 lbs. (2,114 kg)	4,862 lbs. (2,205 kg)	5,205 lbs. (2,361 kg)	5,520 lbs. (2,504 kg)	5,850 lbs. (2,654 kg)
<b>Tines</b>	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)
<b>Tine Spacing</b>	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
<b>Chopper Reel</b>	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
<b>Reel Bearings</b>	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
<b>Reel Protection</b>	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
<b>Number of Sections</b>	2	2	2	2	3	3	3	3	3
<b>Independent Hydraulic Lift</b>	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
<b>Weight Kit Required</b>	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed	Yes, 3 Needed