



2400 Series Weatherproofer (WP1) Specifications

Chopper Reel Attachment

Adapts To:	2410-6-24	2410-7-24	2410F-7-24	2410AFG-7-24	2410-9-24	2410F-9-24	2410AFG-9-24	2430-11-24	2430-13-24
Approximate Weight	1,430 lbs. (649 kg)	1,680 lbs. (762 kg)	1,680 lbs. (762 kg)	1,680 lbs. (762 kg)	1,935 lbs. (878 kg)	2,135 lbs. (968 kg)	2,135 lbs. (968 kg)	2,380 lbs. (1,080 kg)	2,560 lbs. (1,161 kg)
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Reel Protection	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
Independent Hydraulic Lift	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Section Width	8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m)	9 ft. 6 in. (2.9 m) -- 9 ft. 6 in. (2.9 m)	6 ft. 10 in. (2.1 m) -- 6 ft. 10 in. (2.1 m) -- 6 ft. 10 in. (2.1 m)	6 ft. 10 in. (2.1 m) -- 6 ft. 10 in. (2.1 m) -- 6 ft. 10 in. (2.1 m)	10 ft. 9 in. (3.3 m) -- 10 ft. 9 in. (3.3 m)	8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m)	8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m) -- 8 ft. 1 in. (2.5 m)	7 ft. 7 in. (2.3 m) -- 10 ft. 9 in. (3.3 m) -- 7 ft. 7 in. (2.3 m)	9 ft. 5 in. (2.9 m) -- 10 ft. 9 in. (3.3 m) -- 9 ft. 5 in. (2.9 m)