



2400 Series Weatherproofer (WP1) Specifications

Combo Tine and Chopper Attachment

Adapts To:	2410-6-24	2410-7-24	2410F-7-24	2410AFG-7-24	2410-9-24	2410F-9-24	2410AFG-9-24	2430-11-24	2430-13-24
Approximate Weight	2,880 lbs. (1,306 kg)	3,170 lbs. (1,438 kg)	3,740 lbs. (1,696 kg)	3,740 lbs. (1,696 kg)	3,350 lbs. (1,520 kg)	3,920 lbs. (1,778 kg)	3,920 lbs. (1,778 kg)	4,590 lbs. (2,082 kg)	4,915 lbs. (2,229 kg)
Tines	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)	0.625 in. x 24 in. (15.9 x 610 mm)
Tine Spacing	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center	4 in. (102 mm) on Center
Chopper Reel	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter	5-Blade, 16 in. (406 mm) Diameter
Reel Bearings	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals	C-Cushion Trunnion Mount, Greaseable Triple Lip Seals
Reel Protection	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex	Individual Arm Mounted Adjustable Springs with C-Flex
Independent Hydraulic Lift	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard
Section Width	8 ft. (1.8 m) -- 8 ft. (1.8 m)	8 ft. (1.8 m) -- 10 ft. (3.0 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m)	6 ft. (1.8 m) -- 6 ft. (1.8 m) -- 6 ft. (1.8 m)	10 ft. (3.0 m) -- 10 ft. (3.0 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	8 ft. (2.4 m) -- 6 ft. (1.8 m) -- 8 ft. (2.4 m)	6 ft. (1.8 m) -- 14 ft. (4.3 m) -- 6 ft. (1.8 m)	8 ft. (2.4 m) -- 14 ft. (4.3 m) -- 8 ft. (1.8 m)