



## Power Ditcher Specifications

Product Attributes	D4P16A	D5P18A	D10P18A	D10PH18A
Approximate Weight	355 lbs. (161 kg)	525 lbs. (238 kg)	525 lbs. (238 kg)	530 lbs. (240 kg)
PTO RPM	540 RPM	540 RPM	1,000 RPM	1,000 RPM
PTO Coupler Size	1.375 in. (34.9 mm)	1.375 in. (34.9 mm)	1.375 in. (34.9 mm)	1.75 in. (44.5 mm)
Shear Bolt Size	0.3125 in. (7.9 mm) Grade 8	0.375 in. (9.5 mm)	0.375 in. (9.5 mm)	0.375 in. (9.5 mm)
Cutter Head Speed	540 RPM	740 RPM	740 RPM	740 RPM
Adjustable Cutter Head	16 in. to 18 in. (406 to 458 mm)	18 in. to 20 in. (458 to 508 mm)	18 in. to 20 in. (458 to 508 mm)	18 in. to 20 in. (458 to 508 mm)
Cutter Blades	(4) Replaceable Heat Treated	(4) Replaceable Heat Treated	(4) Replaceable Heat Treated	(4) Replaceable Heat Treated
Chain Case	3 in. x 8 in. (76 x 203 mm)	6 in. x 10 in. (152 x 254 mm)	6 in. x 10 in. (152 x 254 mm)	6 in. x 10 in. (152 x 254 mm)
Chain	#80 H	Double #80	Double #80	Double #80
Sprockets	15 Tooth Hardened	16 and 22 Tooth Hardened	16 and 22 Tooth Hardened	16 and 22 Tooth Hardened
Three-Point Hitch	Cat. I, II or Cat. II Quick Hitch	Cat. II, III or Quick Hitch	Cat. II, III or Quick Hitch	Cat. II, III or Quick Hitch
Depth of Operation	Depth Skid and Three-Point Adjustable	Depth Skid and Three-Point Adjustable	Depth Skid and Three-Point Adjustable	Depth Skid and Three-Point Adjustable
Parking Stands	(2) Standard	(2) Standard	(2) Standard	(2) Standard
Powder Coat Paint, Sapphire Blue	Standard	Standard	Standard	Standard
Horsepower Requirements	35 to 60 HP (26 to 45 kW)	50 to 100 HP (37 to 75 kW)	80 to 150 HP (60 to 112 kW)	80 to 150 HP (60 to 112 kW)