

CTS TRACTOR

Reduce your compaction zones and increase traction

Engineered to easily convert tractors to tracks. With excellent traction and flotation in wet or soft ground conditions, it's a perfect choice for tillage and rice fields.





Front Track Width 24"

Sprocket

To get the most power to the ground

 Positive drive sprocket designed to engage up to 8 drive lugs

Main frames

Simplifies maintenance operations

Oil bath drive hubs

Suspension

 Patented double oscillating bogie wheels

Hydraulic tensioning system

Maximizes tractive performance hydraulic tensioning system with nitrogen-charged accumulator

 Maintains track tension for each system independently

Track

Improves traction

 Designed with a large track footprint to reduce ground pressure and high traction tread pattern

Wheels

Simplifies maintenance operations

- Heavy duty wheel hubs with oil bath lubrication
- No greasing or repacking of bearings

Improves ground contact on uneven terrain to help transfer power to the ground


10 |

CAMSO CTS TRACTOR

TRACK SYSTEM FRONT


24D18C

Track width	24"
Track system height	53.8"
Track system length	82.1"
Flat plate area per pair (in²)	2,568



TRACK SYSTEM REAR 30D23MC

Track width	30"
Track system height	64.6"
Track system length	85.2"
Flat plate area per pair (in²)	3,402



Camso provides comprehensive warranty coverage for a period of 12 months from date of purchase, for Conversion Track System (CTS) against defects in materials and workmanship. Some conditions apply. Refer to the warranty certificate for details. For more info, visit **camso.co/agriculture**

