

**LEAD  
THE  
FIELD.**

## 13XL+ & 13HP+ Swing Away Augers



### Move Faster. Reach Further.

Spend less time at the bin and more time in the field with Brandt's 13" Swing Away Augers. The XL+ and HP+ augers provide the optimal fit and versatility needed for any farm and are available in 70', 80', 90', and 110' lengths. 13XL+ models deliver an impressive 11,000 bu/hr, while the HP+ models deliver an industry-leading 13,000 bu/hr.

#### ① Better Performing

Brandt swing away augers are faster than ever to ensure you get more done in less time:

- HP+ models optimize the flow of grain from the hopper through the 14" swing tube and into the 13" main auger resulting in industry-leading capacities with less flow-resistance.
- Move your crop, not your trailer with the all-new, fastest-ever EZReach extendable swing hopper for 13HP+ augers, featuring a 25% larger hopper to speed up your operation.
- Brandt's extended-life auger flighting is thicker at the edges where the most wear typically occurs to keep your auger running longer and more efficiently.

#### ② Easier To Use

The user-friendly design ensures you stay productive during a fast-paced harvest:

- The EZSWING hopper mover is available with electric controls to guarantee easy maneuvering with a remote control or the LeadHand mobile app.
- The heavy-duty scissor lift delivers maximum reach, clearance, and low transport height while a standard monotube undercarriage improves safety, stability, and product life.
- The 70" x 40" hopper makes positioning under trailer hoppers easier than ever. And, it features flat-free tires for trouble-free use during harvest.

#### ③ Longer Lasting

Protect your investment with Brandt's innovative design:

- Two robust easy access clean-out doors on the transition ensure easy maintenance. And, the transition spout is sealed completely to keep your product in and moisture out.
- Designed with a chain coupler between the swing tube flighting and the gearbox for worry-free maintenance. The coupler absorbs shocks and protects the gearbox, increasing its longevity.
- Brandt's superior powder-coat paint optimizes cleanout, rust protection, and component life to increase your resale value.

Powerful Value. **Delivered.**

**Brandt**

# 13XL+ & 13HP+ SWING AWAY AUGERS

## SPECIFICATIONS

	1370XL+	1380XL+	1390XL+	13110XL+	1370HP+	1380HP+	1390HP+	13110HP+
<b>Performance</b>								
Capacity (bushels per hour)	11,000	11,000	11,000	11,000	13,000	13,000	13,000	13,000
Recommended Horsepower	150	160	170	180	175	195	215	235
Tractor PTO RPM	540	540	540	540	1,000	1,000	1,000	1,000
<b>Dimensions</b>								
Diameter – Tube / Swing Away	13" / 13"	13" / 13"	13" / 13"	13" / 13"	13" / 14"	13" / 14"	13" / 14"	13" / 14"
Length	70'	80'	90'	110'	70'	80'	90'	110'
Height – Lowered / Raised	9' 6" / 48' 7"	10' 9" / 55' 3"	11' 11" / 61' 11"	12' 10" / 73'	9' 6" / 48' 7"	10' 9" / 55' 3"	11' 11" / 61' 11"	12' 10" / 73'
Reach – Lowered / Raised	33' 3" / 22' 9"	43' 1" / 29' 6"	53' / 36' 11"	61' 9" / 46' 2"	33' 3" / 22' 9"	43' 1" / 29' 6"	53' / 36' 11"	61' 9" / 46' 2"
Transport Length	72' 9"	82' 8"	92' 9"	112' 6"	72' 9"	82' 8"	92' 9"	112' 6"
Transport Height	13' 2"	13' 2"	13' 8"	15' 3"	13' 2"	13' 2"	13' 8"	15' 3"
Wheel Track Width	12' 4" - 14' 10"	12' 4" - 14' 10"	12' 4" - 14' 10"	13' 4" - 16' 4"	12' 4" - 14' 10"	12' 4" - 14' 10"	12' 4" - 14' 10"	13' 4" - 16' 4"
Tube Thickness	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga	12 ga
Flighting – Main / Swing Away	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"	1/4" / 3/8"
Core Diameter	3"	3"	3"	3"	3"	3"	3"	3"
Lower Bearing Size	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
Gearbox Shaft Diameter	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"	1-3/4"
Weight – Hitch / Total (lb)	1,500 / 6,300	1,270 / 6,900	1,050 / 7,100	1,510 / 9,300	1,700 / 6,500	1,470 / 7,100	1,210 / 7,300	1,740 / 9,500
<b>Undercarriage</b>								
Lift Mechanism	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor	Scissor
Frame Arms	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated	Fabricated
Axle	4"x4"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4.5"x4.5"x3/16"	4"x6"x3/16"
Hydraulic Cylinder Size	4" x 36"	5" x 36"	5" x 36"	5" x 36"	4" x 36"	5" x 36"	5" x 36"	5" x 36"
Number of Hydraulic Cylinders	2	2	2	2	2	2	2	2
Hydraulic Requirements (psi)	1,050	1,100	1,600	1,950	1,050	1,100	1,600	1,950
Tire Size	ST225/75R15	ST235/85R16	ST235/85R16	ST235/85R16	ST225/75R15	ST235/85R16	ST235/85R16	ST235/85R16
Tire Ply Rating	8 Ply	8 Ply	8 Ply	12 Ply	8 Ply	8 Ply	8 Ply	12 Ply
<b>Self-Leveling Swing Away Hopper</b>								
Length x Width x Height	70"x 40"x10"	70"x40"x10"	70"x40"x10"	70"x40"x10"	70"x 40"x10"	70"x40"x10"	70"x40"x10"	70"x40"x10"
Height w/ Extension	17"	17"	17"	17"	17"	17"	17"	17"
# of Horizontal Flights	2	2	2	2	2	2	2	2
# of Wheels	4	4	4	4	4	4	4	4
Wheel Size	10"	10"	10"	10"	10"	10"	10"	10"

## OPTIONS

Man/hyd/elec winch

Man/hyd/elec EZSWING hopper mover

AugerSteer hydraulic steering kit

Right angle drive

Reversing kit (13XL+)

Safety light kit

Hopper Cover

Work light kit

For more information  
Call us at 1-866-4-BRANDT  
Email us at [agriculture@brandt.ca](mailto:agriculture@brandt.ca)  
Or visit us at [www.brandt.ca](http://www.brandt.ca)

**Brandt Agricultural Products**  
PO Box 317, 13th Avenue & Pinkie Road,  
Regina, SK, Canada  
S4P 3A1

