



Field



Fleet



Irrigate



Dashboard




Productivity & Delay



Operator Login



Display Settings



Calculator



Browser

9:39 AM TUESDAY
9 DECEMBER 2014



agrometius



myAg

Trimble



TRIMBLE® TMX-2050™ DISPLAY

System

DC Power Supplied by TM-200, 27 Volts, 3.5 Amps
Processor 1 GHz quad core
Storage Primary embedded memory – 32 GB

Mechanical

Dimensions. 312 x 214 x 45 millimeters (12.3 x 8.4 x 1.8 inches)
(plus connectors)
Weight 2.5 kg (5.5 lb)
Mount. 4 M6 screws on 75 mm centers (3 inch)

Housing

Material Magnesium
Environmental Rating. IP55

Temperature

Operation 0 °C to 65 °C (32 °F to 149 °F)
Storage -40 °C to 85 °C (-40 °F to 185 °F)

LCD Display

Size (diagonal)..... 307 mm (12.1 inch)
Touchscreen Protective capacitive touch
Resolution 1280 x 800
Brightness (adjustable)..... 1000 candela/m²

Front Facing Camera

Type. Low light level, color
Resolution 1.3 Megapixels

Connections

USB (1 side facing, 1 rear facing) USB 2.0
Ethernet (via TM-200)..... RJ45 Connector
CAN (sources 5VDC) RJ11 Connector
Port Expander (optional) 1 Port for CAN bus, I/O, and Serial
HDMI Output. DVI Connector

