MONTAG GEN II 2208 DRY PRODUCT METERING SYSTEM

(AVAILABLE AS SINGLE OR DUAL PRODUCT)

GEN II 2208 Specifications

Row Configurable: 2-8 rows

Section Configurable: 1-4 sections

Slidegate Control Configurable:

Manual Lever or Hydraulic Control

Bin Size Configurable: 30 ft³ or 50 ft³

Product Capacity (bin/total):

30 ft³ bin: 34.8/69.6 ft³ [985/1,971 L], 1.11/2.22 ton [1,007/2,014 kg]* 50 ft³ bin: 55.1/110 ft³ [1,560/3,120 L], 1.76/3.52 ton [1,597/3,193 kg]*

Rate Capacity (bin/total)[†]: 25-500/50-800 lb/ac

[28-560/56-897 kg/ha]

Weight[‡]: 1,450-1650 lb [660- 750 kg]

Overall Height (30 ft³ bins/50 ft³ bins): 66.1/83.6 in [167.9/212.3 cm]

Overall Length: 78.0 in [198.1 cm]

Overall Width: 80.5 in [204.5 cm]

Product Fill Inlet Size: 3.00 ft² [0.28m²]

Product Outlet Hose Size: 2.00 in [5.08 cm]

Req. Hydraulic Capacity: 14-18 gpm [53-68 Lpm]

Req. Hydraulic Press.: 2,000 psi [138 bar]



GEN II 2208 with white bins shown above. Other bin color options include gray and yellow. Bins have one fill inlet each and can be independently scaled, or together. All units use the Montag particulate metering system. Multiple U.S. and international patents cover either, or both, this Product and its components.

*Calculated using 64 lb/ft³ product density [1.025 kg/L] †Calculated using 64 lb/ft³ product density, 30 in row spacing, and 5 mph [1.025 kg/L, 76 cm row spacing, and 8 km/h] ‡Unloaded, dry weight (approximated)



3816 461st Avenue, Emmetsburg, IA 50536 (712) 852-4572 | info@montagmfg.com | http://www.montagmfg.com