## **R135**

## **SKID LOADERS**



GEHL.

Capacities		Metric	Imperial
Rated Operating Capacity		612 kg	1349 lb
Rated Operating Capacity with Optional Counterweight		680 kg	1499 lb
Jnladen weight		2327 kg	5130 lb
Weight and dimensions			
Overall Operating Height - Fully Raised	h27	3653 mm	144 in
Height to Hinge Pin – Fully Raised	h28	2790 mm	110 in
Overall Height to Top of ROPS	h17	1930 mm	76 in
Dump angle at full height	a5	40 °	40 °
Dump height	h29	2120 mm	83 in
Overall length with bucket	l16	3048 mm	120 in
Jump reach - Full height		591 mm	23 in
ollback at ground		28°	28°
eat to ground height	h30	846 mm	33 in
Vheelbase	у	950 mm	37 in
Overall width less bucket	b1	1364 mm	54 in
Bucket Width	e1	1372 mm	54 in
Ground clearance	m4	201 mm	8 in
Overall length - Less Bucket	l2	2322 mm	91 in
learance Radius - Front with Bucket	b18	1842 mm	73 in
learance Circle - Front without Bucket	b19	1120 mm	44 in
Clearance Circle - Rear	wa1	1372 mm	54 in
Performances			
ravel speed (unladen)		12.90 km/h	8 mi/h
Wheels			
tandard tyres		10.00x16.5 HD	10.00x16.5 HD
ingine			
ngine brand		Yanmar	Yanmar
ingine model		4TNV88C	4TNV88C
ingine norm		Stage V / Tier 4	Stage V / Tier 4
Gross Power (kW)		34.30 kW	34.30 kW
let Power (kW)		33.20 kW	33.20 kW
Max. torque / Engine rotation		146.20 Nm / 2800 rpm	146.20 Nm / 2800 rpm
Battery		12 V	12 V
Starter (kW)		2.30 kW	2.30 kW
tydraulics			
Standard flow - Auxiliary hydraulics		70 l/min	70 l/min
ank capacities			
uel tank		59.40 l	16 US gal
pisplacement		2.19 l	0.58 US gal
loise and vibration			
Environmental noise (LwA)		101 dB	101 dB
Whole-Body Vibration (ISO 2631-1)		0.81 m/s <sup>2</sup>	0.81 m/s <sup>2</sup>
/ibration to whole hand/arm		< 1.77 m/s²	< 1.77 m/s <sup>2</sup>





Siège Social P.O. Box 179 - One Gehl Way - West Bend, WI, USA 53095 Tel: (262) 334-9461 - Fax: (262) 338-7517 www.gehl.com



This brochure describes versions and configuration options for Gehl products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Gehl reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Gehl dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Gehl and may not be used without authorization. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU EQUIPMENT AMERICAS, LLC - Limited company with board of directors - Share capital: 39,668,399

euros - 857 802 508 RCS West Bend