

Fertilizer Applicator 1840

MODEL	1840
Tank size	1800 gallon, stainless steel baffle, hopper bottom sump
Coulters	<ul style="list-style-type: none"> - Yetter 2996, parallel linkage, 20" coulter w/knife - Yetter 2995 Gen. III, single linkage, 20" coulter w/injector - Hydraulic depth control assist
Tool bar	<ul style="list-style-type: none"> - Available in 20", 22", 30", 38" rows in widths up to 45 ft.; Twin cylinder height adjust - 7 x 7 high-clearance toolbar with 15° down flex; - Adjustable gauge wheels
Tire size	380/90 R46 single and duals, 320/90R46 duals, 320/90R50 singles
Wheel spacing	120" fixed, 132" fixed, 120" - 152" adj. axles
Pumps	<ul style="list-style-type: none"> - John Blue ground driven, twin piston pump - Ace hydraulic centrifugal pump kit w/Raven 450 controller, Raven Viper 4, or ISO Ready - Visual flow monitors, standard
Ground clearance ¹	36"
Transport width ¹	17' 9"
Transport height ¹	13' 3"
Transport length ¹	21' 8"
Empty tongue weight	3,820 lb
Empty weight	12,680 lb
Fresh water safety tank	9 gallon
Quick fill	3"
Pin to axle length	14' 7"
Available colors	Red / Cream Green / Cream

¹ Approximate