

Crop Flail Shredders



BUSH HOG®

IF IT DOESN'T SAY
BUSH HOG®
IT JUST WON'T CUT IT™

BRC SERIES | BRC115, BRC118, BRC120, BRC125



CROP FLAIL SHREDDERS

*BRC
SERIES*

BRC115 / BRC118 / BRC120 / BRC125



The Bush Hog® line of BRC row crop flails provides superior shredding performance in a number of crop conditions. Cotton, BT corn stalks, milo, rice, wheat, and vegetable stubble are no match for these machines. Designed to handle higher volumes of crop residue, the BRC models from Bush Hog® are equipped with a re-cutter bar design which allows the material to be cut three times, thereby speeding up crop decomposition. Computer-balanced 10 3/4-inch diameter rotors ensure smooth operation in tough conditions. Triple-lipped, sealed double row spherical roller bearings, combined with reversible, hard surfaced cutter knives and 3/16-inch internal steel liners at critical wear areas, ensure greater reliability in tough conditions. Bush Hog® units are available in 15-, 18-, 20-, and 25-foot operating widths to match various crop conditions and row spacings. Depending on the model, the BRC row crop flails are available with pull, lift, or semi-mount hitches. These BRC row crop flails are ready to shred!

BRC Series Features

- **Blades chops through cotton**, BT corn stalks, milo, rice, wheat, or vegetable stubble.
- **Re-cutter bar speeds up decomposition** of plant residue to get nutrients back into the ground quickly.
- **Frame provides ground cover** to minimize wind and water erosion.
- **Sizes available in 15-, 18-, 20-, and 25-foot widths** to fit your crop's row spacing.

CROP FLAIL SHREDDER SPECIFICATIONS

MODELS:		BRC115	BRC118	BRC120	BRC125
Cutting Width		180 inches	216 inches	240 inches	300 inches
Overall Width		204 inches	240 inches	264 inches	324 inches
Cutting Height		1 inch to 18 inches			
Hitch Types		CAT II-III QH Lift, Semi-Mount, or Pull Type			Lift, Semi-Mount, or Pull Type
Cutter Shaft Diameter		10 3/4 inches			
Min. PTO HP Required	Lift	120 HP	130 HP		N/A
	Semi-Mount	100 HP	110 HP	120 HP	150 HP
	Pull-Type	100 HP	110 HP	120 HP	140 HP
Gearbox Rating		207 HP			
PTO Type		1,000 RPM			
Blades		Hard Surfaced: No "D" Rings			
Blade Tip Speed (FPM)		12,620			12,000
No. of Blades		168	200	216	272
Driveline Size		Category 5 or 6			
Driveline Protection		5 x 5V Banded Belt			
Rotor Bearing Protection		Anti-Wrap Seal Protector			
Cutter Shaft Bearings		2 9/16-inch Double Row Spherical Roller, Triple Sealed			
Hood Thickness		3/16 inch with 3/16 inch Internal Wear Liner			
End Plate Thickness		1/4 inch			
Number of Axles		4			
Wheel Hub Size		5 bolt		6 bolt	
Tire Size/Type		6.70-5 Ribbed		9.5L-15 Ribbed	
Safety Lights		Standard			
Weight (Approximate)		4,600 lbs.	4,960 lbs.	5,150 lbs.	6,300 lbs.



IF IT DOESN'T SAY
BUSH HOG®
IT JUST WON'T CUT IT™

2501 Griffin Avenue, Selma, Alabama 36703

Tel: 800-363-6096 | Fax: 334-874-2701

www.bushhog.com

