



# Delivery Box • Feeder Box RT • RTX SERIES

Front Unload • Front & Rear Unload



**RT216**



**RT518**

## Trailer Mount • Wagon Mount • Truck Mount



**RTX226**



**RT220**

### RT Series

- Welded frame on 24" spacing
- 667H pintle aprons – RT500
- 667X pintle aprons – RT600/RT200
- 51" std inside height / optional 66"
- 2 auger std / 3 auger opt with 15" taller side

### RTX SERIES

- Welded frame on 16" spacing
- 667X pintle aprons
- 74" inside height / optional 86"
- 3rd auger std / 4th opt with 12" taller side


### Built to Last! (RT & RTX Models)

- Clad-Tuff fiberglass side panels
- Solid, high molecular poly floor
- Poly lined cross conveyor
- Massive formed top rail/cap on sides
- HD bevel gear drive apron & augers
- Lower 2x6 rub rail is standard

**DESIGNED & MANUFACTURED TO ACCOMMODATE  
TODAY'S DEMANDING OPERATIONS!**

More Sizes • More Options • More Strength & Capacity!

**Farm Equipment Buyers Trust the Name Meyer!**





# Dimensions • Specifications • Options



## Standard Direct Drive

- This simple direct drive system allows for basic on/off operation. Conveyor/Augers have a soft start followed by Independent Apron Engagement.
- Std system is PTO powered/opt hyd
- Rear unload models are hyd drive



## Basic Hydraulic Drive

- Available on all front unload models
- Same controls as std direct drive
- This package replaces the PTO Driveline with a hyd motor & hoses. This eliminates hooking/unhooking PTO between loads.
- Rear unload models are hyd drive



## Cab-Control Hydraulic Drive

- Available on all front unload models
- All hyd/elec controls from truck/tractor
- Requires 25gpm/3,000 psi
- Hydraulic lift conveyor standard
- Less moving parts/maintenance
- Rear unload models are hyd drive



## Discharge

- 36" fold-down cross conveyor std
- Extends down 36" (from side of box)
- Designed to run flat/at mild angles
- Manual lift, shock assist std/hyd opt
- Left discharge (std) or Right discharge available



## Scale Packages

- Available for all models/applications Truck – Trailer – Wagon Mount
- Multiple Indicator Choices
- Optional remote TR/remote displays



## 8200RT Commercial Model

- Premium 8200RT BOSS model
- 22-24-26' Front & Rear Unload only
- 8' interior width, 16" frame spacing 72" or 86" inside height
- Commercial Grade drive components/ cab control drive

	Heavy Duty Front Unload			Industrial Duty Front Unload • Front/Rear Unload				Commercial Grade Front Unload • Front/Rear Unload			
	RT514 front	RT516 front	RT518 front	RT616 front RT216 f/r	RT618 front RT218 f/r	RT620 front RT220 f/r	RT622 front RT222 f/r	RTX620 front RTX220 f/r	RTX622 front RTX222 f/r	RTX624 front RTX224 f/r	RTX626 front RTX226 f/r
Floor Length	14'6"	16'6"	18'6"	16'6"	18'6"	20'6"	22'6"	20'6"	22'6"	24'6"	26'6"
Overall Length (box only)	17'4"	19'4"	21'4"	19'4" - RT616 20'2" - RT216	21'4" - RT618 22'2" - RT218	23'4" - RT620 24'2" - RT220	25'4" - RT622 26'2" - RT222	23'4" - RTX620 24'2" - RTX220	25'4" - RTX622 26'2" - RTX222	27'4" - RTX624 28'4" - RTX224	29'4" - RTX624 30'4" - RTX224
Main Pintle Apron	667H x 4	667H x 4	667H x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4	667X x 4
Upright-Crossmember	24"	24"	24"	24"	24"	24"	24"	16"	16"	16"	16"
Spacing/Frame design	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded	Welded
HD Bevel Style Auger & Apron Drive	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard	Standard

## RT Series Specifications:

Power Source	Hyd Drive (opt), PTO Drive (std) Hyd Cab Control Drive (opt)
Hydraulic Requirements	(20/25 gpm, 3000 psi) Front Unload
Augers (not spiral beaters)	2 Lg 18" Dia Augers Tapering into Box (w/std 51" sides) - RT Models 3 Lg 18" Dia Augers Tapering into Box (w/opt 66" sides) - RT Models
Cross Conveyor	D662 Pintle w/Angle Cross Slat & Hold-Downs (Poly Lined)
Discharge	Left Hand std – Right Hand opt
Discharge Clearance	w/36" Conveyor Extension

Minimum (down 0)	43.5" (on XT1600 Trailer w/riser/trk/tires) +5" for XT2200
Maximum (up 45)	60" (on XT1600 Trailer w/riser/trk/tires) +5" for XT2200
Inside Width	7'5" (RT & RTX)
Inside Height	Standard 51" (RT)
(RT) Top Rail Kit	57" w/opt Treated Wood
Height from Bottom of Stringers to Top of Box (RT Pull type)	Add 15" for 15" Taller Side opt 70" Standard Sides
Overall Width	76" w/opt Treated Wood Top Rail Kit Add 15" for 15" Taller Side opt (w/std 36" conveyor extension)

Conveyor Up	9'2"
Conveyor Down	11'
Side Material	Clad Tuff Woven Fiberglass (White)
Floor Material	Solid, High Molecular Poly Floor
Lower Rub Rails	Std-Treated 2x6, Runs Full Length
Emergency Stop/Cut-out	Standard-Front Unload
Light Package	Standard w/Cord
Truck Mount Version	Opt-Call Factory for Truck Specs
24" Conveyor Ext.	Opt/In Lieu of Std 36"
Scale Packages	Optional

**RTX Series Feeder boxes** avail w/74"/86" inside height only. Call factory for specifications and details.

• Specifications subject to change without notice • Truck mount requirements available on our website or call factory.

See [meyermfg.com](http://meyermfg.com) or Running Gear/Ag Trailer brochure for details and specs on appropriate undercarriage for your Meyer Delivery Box.

YOUR DEALER IS:



Connect with us!

# Meyer Mfg. Corp.

Dorchester, Wisconsin 54425

Phone: 715/654-5132 • FAX: 715/654-5513 • 1-800-325-9103

email: [sales@meyermfg.com](mailto:sales@meyermfg.com) • [www.meyermfg.com](http://www.meyermfg.com)